MICROCOPY RESOLUTION TEST CHART

NATIONAL BUREAU OF STANDARDS 1963 A

NAVAL POSTGRADUATE SCHOOL
Monterey, California

DTIC
ELECTE
JUN 1 4 1985
S   D
B

THESIS

TARGET VULNERABILITY
TO AIR DEFENSE WEAPONS

by

Bruce Edward Reinard

December 1984

Thesis Advisor: R. E. Ball

Approved for public release;   distribution unlimited

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) Target Vulnerability to Air Defense Weapons		5. TYPE OF REPORT & PERIOD COVERED Master's Thesis December 1984
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) Bruce Edward Reinard		8. CONTRACT OR GRANT NUMBER(s)
9. PERFORMING ORGANIZATION NAME AND ADDRESS Naval Postgraduate School Monterey, California 93943		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
11. CONTROLLING OFFICE NAME AND ADDRESS Naval Postgraduate School Monterey, California 93943		12. REPORT DATE December 1984
		13. NUMBER OF PAGES 148
14. MONITORING AGENCY NAME & ADDRESS(if different from Controlling Office)		15. SECURITY CLASS. (of this report)
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE

16. DISTRIBUTION STATEMENT (of this Report)

Approved for public release; distribution unlimited

17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)

18. SUPPLEMENTARY NOTES

19. KEY WORDS (Continue on reverse side if necessary and identify by block number)

cont

Aircraft Vulnerability, Aircraft Susceptibility, Vulnerability Assessment, Probability of Kill, P_K, Critical Components.

20. ABSTRACT (Continue on reverse side if necessary and identify by block number)

This thesis is intended to become a portion of the textbook utilized in the course entitled "Warheads and Lethality" (AE-3705). This portion of the text includes an unclassified discussion of a target's susceptibility to an externally detonating HE warhead and a target's vulnerability. In particular, the section on target susceptibility leads to the development of the number of fragments which strike a target

20. Continued.

aircraft from an externally detonating warhead. The section on target vulnerability explains the methodology used for identifying critical components and conducting a vulnerability assessment, and leads to the effects of fragments and penetrators striking an aircraft.

Accession For

NTIS GRA&I	✓
DTIC TAB	☐
Unannounced	☐
Justification	

By

Distribution/

Availability Codes

	Avail and/or
1st	Special

A-1

S-N 0102-LF-014-6601

Target Vulnerability
to Air Defense Weapons

by

Bruce E. Reinard
Lieutenant, United States Navy
B.S., Virginia Military Institute, 1979

Submitted in partial fulfillment of the
requirements for the degree of

MASTER OF SCIENCE IN ENGINEERING SCIENCE

from the

NAVAL POSTGRADUATE SCHOOL
December 1984

Author: _____
Bruce E. Reinard

Approved by: _____
R.E. Ball, Thesis Advisor

_____
A.E. Fuhs, Second Reader

_____
M. F. Platzer, Chairman,
Department of Aeronautics

_____
John N. Dyer,
Dean of Science and Engineering

ABSTRACT

This thesis is intended to become a portion of the textbook utilized in the course entitled "Warheads and Lethality" (AE-3705). This portion of the text includes an unclassified discussion of a target's susceptibility to an externally detonating HE warhead and a target's vulnerability. In particular, the section on target susceptibility leads to the development of the number of fragments which strike a target aircraft from an externally detonating warhead. The section on target vulnerability explains the methodology used for identifying critical components and conducting a vulnerability assessment, and leads to the effects of fragments and penetrators striking an aircraft.

~ ... on keywords include: ...

TABLE OF CONTENTS

6

LIST OF TABLES

LIST OF FIGURES

9

I. SUSCEPTIBILITY TO EXTERNALLY DETONATING FRAGMENTATION WARHEADS

A. INTRCDUCTION

Susceptibility refers to the inability of a target to avoid being damaged in the pursuit of its mission. For aircraft, susceptibility to an externally detonating warhead refers to an aircraft's probability of being hit. Susceptibility, like vulnerability, is good. The level or degree of susceptibility of an aircraft in an encounter with a threat is dependent upon three major factors, the encounter scenario, the threat, and the aircraft. The encounter scenario includes the missile and aircraft positions, velocity vectors, respective attitudes, a determination of the warhead's fragment dynamic spray angles, a determination of the missile miss distance, and the determination of how many fragments or penetrators strike the aircraft. The important features of the threat are its characteristics, its operations, and its lethality. The important aircraft features are the aircraft detectable signatures, countermeasures, performance capabilities, and self-protection armament.

B. ENCOUNTER SCENARIC

The encounter scenario takes into account the missile's flight path and the target's flight path to allow calculation of the missile miss distance, fragment miss distance, the warhead's dynamic fragment spray angles and velocities, and the number of fragments which strike the target.

11

Figure 1.8 Fragment Miss Distance Depicted
in Local Coordinate System

Figure 1.7 Fragment Miss Distance Using Vector
Notation in Global Coordinate System

Figure 1.6 Fragment Miss Distance Depicted
in Global Coordinate System

The derivation of the minimum missile miss distance in the local system follows the same procedure as for the global system, and since it leads to the same result as given by Equation 1.17, the derivation will not be repeated.

From the geometry of Figure 1.5, it is possible to determine if the missile will be a "late bird" or an "early bird". An "early bird" is where the closest point of approach (CPA) of the missile is in front of the target in the local system. A "late bird" is where the CPA of the missile is behind the target. This relationship may be determined graphically with the use of the following formula:

$$\tilde{\theta} = Tan^{-1} [(V_m \ x \ Sin\theta) / [(V_m \ x \ Cos\theta) - V_t]] \qquad (1.22)$$

Now that the missile miss distance has been calculated, and knowing the fragment spray density, a determination must be made as to whether or not the fragments hit the target, and if so, how many fragments strike the target. To accomplish this, the fragment miss distance must be determined.

4. Fragment Miss Distance

As was the case for missile miss distance, the fragment miss distance may be derived in either a global coordinate system or in a local coordinate system. Figure 1.6 depicts the fragment miss distance for the global coordinate system, and Figure 1.7 depicts the miss distance for the global system using vector notation. Figure 1.8 depicts the fragment miss distance in the local coordinate system. The derivation of the fragment miss distance in a global coordinate system follows. Referring to Figure 1.7, and using vector addition, the fragment miss distance, $\overline{c}$, is given by Equation 1.23.

22

Figure 1.5   Encounter Scenario in the Local System

Of interest is the minimum miss distance. Taking the derivative of Equation 1.17 with respect to τ, and setting it equal to zero yields:

$$[(\{T_x - M_x\} \times \{V_t - (V \times \cos\theta)\}) - \{(T_y - M_y) \quad (1.18)$$
$$\times (V_m \times \sin\theta)\}] + [\tau \times [\{V_t - (V_m \times \cos\theta)\}^2$$
$$+ (V_m \times \sin\theta)^2]] = 0$$

Solving Equation 1.18 for τ yields τ for the minimum miss distance which is:

$$= [((T_y - M_y) \times V_m \times \sin\theta) + ((T_x - M_x) \quad (1.19)$$
$$\times V_m \times \cos\theta) - ((T_x - M_x) \times V_t)] /$$
$$[(V_t - (V_m \times \cos\theta))^2 + (V_m \times \sin\theta)^2]$$

The minimum missile miss distance is then given by substituting the value of τ, obtained from Equation 1.19, into Equation 1.17.

b. Local Approach

The local approach is an alternative approach to the one described above. In the local approach, the target remains stationary and the target's velocity vector is superimposed on the missile's velocity vector. This geometry is depicted in Figure 1.5. From Figure 1.5, the velocity of the missile with the target's velocity superimposed, $\bar{V}_{mt}$, becomes:

$$\bar{V}_{mt} = (V_m \times \cos\theta)\hat{i} + (V_m \times \sin\theta)\hat{j} - (V_t)\hat{i} \quad (1.20)$$

Rearranging Equation 1.20 into a more suitable form gives:

$$\bar{V}_{mt} = [(V_m \times \cos\theta) - V_t]\hat{i} + [V_m \times \sin\theta]\hat{j} \quad (1.21)$$

20

$$\bar{T} + \bar{t} = \bar{M} + \bar{m} + \bar{s} \qquad (1.9)$$

Rearranging Equation 1.9 and solving for $\bar{s}$ leads to:

$$\bar{s} = (\bar{T} - \bar{M}) + (\bar{t} - \bar{m}) \qquad (1.10)$$

The initial conditions (at time $t = 0$) are given by Equations 1.11 and 1.12. The conditions at some later time ($t = \tau$) are given by Equations 1.13 and 1.14.

$$\bar{T} = (T_x)\hat{i} + (T_y)\hat{j} \qquad (1.11)$$

$$\bar{M} = (M_x)\hat{i} + (M_y)\hat{j} \qquad (1.12)$$

$$\bar{t} = (V_t \times \tau)\hat{i} \qquad (1.13)$$

$$\bar{m} = (V_m \times \tau \times \cos\theta)\hat{i} + (V_m \times \tau \times \sin\theta)\hat{j} \qquad (1.14)$$

Substituting these conditions back into Equation 1.10 gives:

$$\bar{s} = [(T_x - M_x)\hat{i} + (T_y - M_y)\hat{j}] + [((V_t \times \tau) \qquad (1.15)$$
$$- (V_m \times \tau \times \cos\theta))\hat{i} - (V_m \times \tau \times \sin\theta)\hat{j}]$$

Rearranging Equation 1.15 and combining similar components gives:

$$\bar{s} = [(T_x - M_x) + [\tau \times (V_t - (V_m \times \cos\theta))]]\hat{i} \qquad (1.16)$$
$$+ [(T_y - M_y) - (V_m \times \tau \times \sin\theta)]\hat{j}$$

The missile miss distance is given by taking the magnitude of Equation 1.16 which is:

$$|s| = [(T_x - M_x) + [\tau \times (V_t - (V_m \times \cos\theta))]]^2 \qquad (1.17)$$
$$+ [(T_y - M_y) - (V_m \times \tau \times \sin\theta)]^2$$

19

Figure 1.4   Global System Encounter Scenario
Using Vector Notation

Figure 1.3 Typical Encounter Scenario
in the Global System

$$\rho = N / A \tag{1.5}$$

where N is the total number of fragments in the warhead and A is the area the fragments are spread over. Referring to Figure 1.2, the area, A, is given by:

$$A = 2 \times \pi \times \int_{\phi_1}^{\phi_2} (s \times Sin \, \phi) \times s \, d\phi \tag{1.6}$$

Solving Equation 1.6 leads to the solution:

$$A = 2 \times \pi \times s^2 \times (Cos \, \phi_1 - Cos \, \phi_2) \tag{1.7}$$

Substituting Equation 1.7 into Equation 1.5 yields the fragment spray density at some distance s from the detonation point:

$$\rho = N / [2 \times \pi \times s^2 \times (Cos \, \phi_1 - Cos \, \phi_2)] \tag{1.8}$$

where the leading and trailing dynamic fragment spray angles are defined, with respect to the warhead axis, by Equation 1.4.

3. Missile Miss Distance

For the calculation of missile miss distance, it is assumed that the encounter is two dimensional, and that the target's velocity and the missile's velocity remain constant. Two approaches to calculate the miss distance will be presented. The first approach is the global approach.

a. Global Approach

Figure 1.3 depicts a typical encounter situation. Figure 1.4 depicts the same encounter situation using vector notation. Referring to Figure 1.4, and using vector addition, the missile miss distance, $\bar{s}$, is given by Equation 1.9.

16

Figure 1.2   Sample Encounter with a Horizontally Moving
Aircraft Depicting the Fragment Spray Density

15

Again referring to Figure 1.1, the dynamic fragment velocity may be written in vector notation as:

$$V_i = [V_m + (V_s \times Cos\alpha_i)]i + [V_s \times Sin\alpha_i]j \qquad (1.3)$$

Solving Equation 1.3 for the dynamic fragment spray angle, ϕ_i, yields:

$$\phi_i = Tan^{-1}[(V_s \times Sin\alpha_i) / [V_m + (V_s \times Cos\alpha_i)]] \qquad (1.4)$$

Now that the dynamic fragment spray angles and velocities are known, the fragment spray density may be determined.

2. Fragment Spray Density

The damage inflicted on an aircraft depends on the number and the location of the fragment impacts, and on the terminal effects parameters such as the fragment mass and impact velocity. For this derivation of the fragment spray density, the following assumptions are made:

1. The fragments lie on a spherical segment whose center is at the center of the warhead.
2. The fragments emerge from the warhead in such a way that they remain on the surface of an expanding sphere.

An encounter scenario with a horizontally moving aircraft, and based on the assumptions stated above, is depicted in Figure 1.2.

For any given fragment spray zone, the density of fragments within that zone is simply the number of fragments contained in the zone divided by the surface area of the sphere contained within the conical angles defining the zone. The average number of fragments per unit area of fragment spray, known as the fragment spray density, ρ, is given by Equation 1.5.

14

Figure 1.1 Typical Warhead Depicting
Dynamic Spray Angles and Velocities[9]

1. Warhead Dynamic Spray Angles and Velocities

When a warhead detonates in the vicinity of an aircraft, the fragments or penetrators are usually ejected uniformly around the missile axis and propagate outward in a divergent spherical-like spray pattern at a velocity that is the vector sum of the initial fragment ejection velocity from a static warhead detonation and the missile velocity. The fragment at the front of the warhead is assumed to propagate outward at the leading spray angle, and the fragment at the tail end of the warhead is assumed to propagate along trajectory at the trailing spray angle. All other fragment trajectories lie between these two spray angles and constitute the fragment spray. As the aircraft moves in space, the fragments propagate outward and eventually some of the fragments may strike the aircraft. Whether or not any of the fragments strike the aircraft and where they hit depend upon the relative positions, velocities, and the attitude of the warhead and the aircraft at the time of detonation (encounter conditions) and the fragment static velocities and static spray angles. A sample warhead depicting static fragment spray angles and velocities, and dynamic fragment spray angles and velocities is depicted in Figure 1.1. Using the law of cosines and Figure 1.1, the dynamic fragment velocity, V_i, is given by:

$$V_i^2 = V_m^2 + V_s^2 - (2 \times V_m \times V_s \times \cos\beta) \qquad (1.1)$$

where V_m is the missile velocity and V_s is the static fragment velocity. Since the angle β is not known, Equation 1.1 must be rearranged to use the only known angle, which is the static fragment spray angle, α. Rearranging Equation 1.1, the dynamic fragment velocity is given by:

$$V_i^2 = V_m^2 + V_s^2 - [2 \times V_m \times V_s \times \cos(180-\alpha_i)] \qquad (1.2)$$

12

$$\overline{c} = (\overline{T} - \overline{F}) + (\overline{t} - \overline{f}) \tag{1.23}$$

The initial conditions are given by Equations 1.24 and 1.25. The conditions at some later time $(t = \tau)$ are given by Equations 1.26 and 1.27.

$$\overline{T} = (T_x)\widehat{i} + (T_y)\widehat{j} \tag{1.24}$$

$$\overline{F} = (F_x)\widehat{i} + (F_y)\widehat{j} \tag{1.25}$$

$$\overline{t} = (V_t \times \tau)\widehat{i} \tag{1.26}$$

$$\overline{f} = (V_i \times \tau \times Cos\,\gamma)\widehat{i} + (V_i \times \tau \times Sin\,\gamma)\widehat{j} \tag{1.27}$$

Substituting these conditions back into Equation 1.23, and solving for $\overline{c}$, leads to:

$$\overline{c} = [\,(T_x - F_x) - (\tau \times ((V_i \times Cos\,\gamma) - V_t))\,]\widehat{i} \tag{1.28}$$
$$[\,(T_y - F_y) - (\tau \times V_i \times Sin\,\gamma)\,]\widehat{j}$$

The magnitude of Equation 1.28 is:

$$|c| = [\,(T_x - F_x) - \{\tau \times ((V_i \times Cos\,\gamma) - V_t)\}\,]^2 \tag{1.29}$$
$$+ [\,(T_y - F_y) - (\tau \times V_i \times Sin\,\gamma)\,]^2$$

To find the minimum fragment miss distance, τ for the minimum miss distance is needed. Taking the derivative of Equation 1.29 with respect to τ, and setting it equal to zero yields:

$$\tau = [\,\{(T_x - F_x) \times \{(V_i \times Cos\,\gamma) - V_t\}\} + \tag{1.30}$$
$$\{(T_y - F_y) \times V_i \times Sin\,\gamma\}\,] \,/\, [\,((V_i \times Cos\,\gamma) - V_t)^2$$
$$+ (V_i \times Sin\,\gamma)^2\,]$$

26

To find the minimum fragment miss distance, simply solve Equation 1.30 for τ, and substitute that value of τ into Equation 1.29. This derivation assumed that the fragment velocity was constant. If the fragment velocity is not constant, or reasonably so, then $\bar{f}$ is given by:

$$\bar{f} = \int_0^\tau [(V_i \times \cos\gamma)i + (V_i \times \sin\gamma)j] \, d\tau \qquad (1.31)$$

Solving Equation 1.31 gives:

$$\bar{f} = [(\cos\gamma)i + (\sin\gamma)j] \times \int_0^\tau Vi(\tau) \, d\tau \qquad (1.32)$$

Now that the fragment miss distance has been calculated, the number of fragments which strike the target will be determined.

5. Fragment Impacts on the Target

The number of hits, n, on the aircraft presented area at the aspect under consideration, A_p, is given by:

$$n = \rho \times A_p \qquad (1.33)$$

where ρ is the fragment spray density defined by Equation 1.8. Figure 1.9 depicts the fragment spray density striking an aircraft in the local coordinate system described earlier, where f_1 and f_2 represent the leading edge and trailing edge fragment vectors, respectively. The angle $\tilde{\gamma}$ is defined as:

$$\tilde{\gamma} = \tan^{-1} [(V_i \times \sin\gamma_i) / ((V_i \times \cos\gamma_i) - V_t)] \qquad (1.34)$$

Figure 1.10 depicts the same geometry in the global coordinate system described earlier. Recall from Equation 1.8 that the distance the fragments travel before striking the

27

Figure 1.9   Fragment Impacts on Aircraft in Local System

Figure 1.10   Fragment Impacts on Aircraft in Global System

aircraft, R, is needed and not R_{det}. The time from detonation to fragment impact in the global system is:

$$t = R / V_i \qquad (1.35)$$

The time from detonation to fragment impact in the local system is:

$$t = R_{det} / V_{ft} \qquad (1.36)$$

where V_{ft} is defined as follows:

$$V_{ft}^2 = [(V_i \times Cos\gamma) - V_t]^2 + [V_i \times Sin\gamma]^2 \qquad (1.37)$$

Equating Equation 1.35 to Equation 1.36, and solving for R yields:

$$R^2 = R_{det}^2 / [1 - (2 \times (V_t/V_i) \times Cos\gamma) \qquad (1.38)$$
$$+ (V_t/V_i)^2]$$

where V_t is the target velocity and V_i is the dynamic fragment velocity as defined by Equation 1.2. The extent of the fragment spray which strikes the aircraft, and the number and location of fragment hits, are dependent upon the encounter conditions. Figure 1.11 depicts the effects of varying the detonation distance to the target. In zone 1, the full fragment spray hits the target. In zone 2, all of the target is hit by part of the fragment spray. In zones 3 and 4, part of the fragment spray hits part of the target. In zone 1, with the target hit by the full fragment spray, the presented area of the aircraft may be determined as follows. Figure 1.12 depicts a frontal view of the fragment spray striking an aircraft. From Figure 1.12, the angle ζ is defined by Equation 1.39.

30

Figure 1.11 Effect of Varying Detonation Distance on
Fragments Impacting on an Aircraft

Figure 1.12   Frontal View of Fragments
Impacting an Aircraft

$$\zeta = Tan^{-1} [W / (2 \times R \times Sin\phi)] \qquad (1.39)$$

The circumferential length of the spray zone is defined as:

$$b = 2 \times \zeta \times R \times Sin\phi \qquad (1.40)$$

where ϕ is the dynamic fragment spray angle of the center fragment.   Substituting Equation 1.39 into Equation 1.40 yields:

$$b = 2 \times R \times Sin\phi \times Tan^{-1} [W / (2 \times R \times Sin\phi)] \qquad (1.41)$$

32

The fragment spray zone covers a spherical area of:

$$\text{Area} = b \times R \times (\phi_2 - \phi_1) \qquad\qquad (1.42)$$

Substituting Equation 1.42 into Equation 1.33 yields:

$$n = (N \times b) / [2 \times \pi \times R \times (\cos\phi_1 - \cos\phi_2)] \qquad (1.43)$$

which determines the number of fragments which strike the aircraft in zone 1. The assumption has been made in this estimation that the fragment spray covers the entire presented area of the aircraft. If this is not the case, or if only a portion of the spray meridian hits a portion of the aircraft (zones 2, 3, and 4 in Figure 1.11), A_p, in Equation 1.33 must be reduced to the actual area that is struck by fragments. The extent of the fragment spray which does strike the aircraft, the number of fragment hits, the fragment approach directions, and where the hits occur are dependent upon the encounter conditions. For example, a detonation directly below the center of the aircraft in a head-on encounter will have a different result than from a detonation in the same place for a tail-chasing missile due to the difference in the relative closing velocity. Furthermore, changing the elevation angle of the missile at the time of detonation will change the results. With the number of fragments which strike the aircraft determined, the effects of fragments and penetrators striking an aircraft will be examined in the next chapter.

33

II. TARGET VULNERABILITY

A. INTRODUCTION

Target vulnerability refers to the inability of a target to withstand one or more hits by damage mechanisms (fragments, penetrators, incendiary particles, and blast) or a target's liability to serious damage or destruction when hit by enemy fire. Aircraft that are more vulnerable are softer, that is, they are more likely to be lost when hit. Therefore, aircraft vulnerability is essentially a measure of the toughness of an aircraft when all surviveability measures have failed and the threat interacts with the aircraft. From an air defense standpoint target vulnerability is good.

Each individual component of an aircraft has a certain level or amount of vulnerability. Each component's vulnerability then contributes, in some measure, to the overall vulnerability of the aircraft. The critical components of an aircraft are those components that are essential to the functioning of a system, and if the component performance is sufficiently degraded or if the component is rendered inoperative by combat damage, a target kill in some kill category will result. The systematic description, delineation, and quantification of the vulnerability of the individual components and vulnerability of the total aircraft is known as a vulnerability assessment.

B. IDENTIFICATION OF CRITICAL COMPONENTS

The first step in a vulnerability assessment is the identification of those components whose damage or loss could lead to an aircraft kill, and they are referred to as

34

critical components. This identification process is called
critical component analysis. A component may be a critical
component because it provides an essential function such as
thrust, lift, or control. A component may also be a crit-
ical component because its mode of failure leads to the
failure of a critical component that does provide an essen-
tial function. For example, a fuel tank in a wing can be
perforated by a fragment, causing a slow fuel leak and even-
tual fuel depletion, with no substantial effect on the
continued operation of the aircraft. In this situation, the
wing fuel tank is not a critical component. On the other
hand, the fragment impact and penetration of the wing tank
could cause ignition of the fuel vapor in the ullage, with a
subsequent fire or explosion and loss of the aircraft. In
this case, the wing tank is definitely a critical component.

A general procedure has been developed for determining
the critical components, their possible damage or failure
modes, and the effects of the component damage or failure
upon the continued operation of the aircraft. This proce-
dure consists of: (1) a selection of the aircraft kill
levels or categories to be considered, (2) an assembly of
the technical and functional description of the aircraft,
and (3) the determination of the critical components of the
aircraft and their damage-caused failure modes for the
selected kill levels.

1. Aircraft Kill Levels

To assess the vulnerability of both fixed wing and
rotary aircraft in-flight, four kill categories have been
defined. These kill categories are the Attrition Kill, the
Mission (Mission Abort) Kill, the Forced Landing Kill, and
the Mission Available Kill.

35

a. Attrition Kill

Attrition kill covers those aircraft with combat damage so extensive that it is neither reasonable nor economical to repair. The attrition category is divided into the six levels of kill listed below.

(1) KK Kill. This level of kill is associated with damage that will cause the aircraft to disintegrate immediately upon being hit. This kill level is also referred to as a Catastrophic Kill.

(2) K Kill. This level of kill is associated with damage that will cause an aircraft to fall out of manned control within 30 seconds after being hit.

(3) A Kill. This level of kill is associated with damage that will cause an aircraft to fall out of manned control within five minutes after being hit.

(4) B Kill. This level of kill is associated with damage that will cause an aircraft to fall out of manned control within 30 minutes after being hit.

(5) C Kill. This level of kill is associated with damage that will cause an aircraft to fall out of manned control before completeing its mission.

(6) E Kill. This level of kill is associated with damage that will cause an aircraft to sustain additional levels of damage upon landing and makes it uneccnomical to repair as specified by the applicable Technical Orders, Technical Bulletins, and regulations.

b. Mission (Mission Abort) Kill

This category covers any aircraft with combat damage that prevents the aircraft from completing its mission. This is mission dependent and is divided into two levels; mission abort and mission kill. Mission abort covers aircraft which are not lost to inventory but cannot

complete their mission. Mission kill covers aircraft which fall cut of manned ccntrol before completing their mission.

c. Forced Landing Kill

This category covers those aircraft with combat damage that forces the crew to execute a controlled landing (powered or unpowered). This category includes aircraft with damage which will require repairs for flight tc anctter area and aircraft with damage which cannot be repaired on site but which can be recovered by a special team. This categcry has been restricted mainly to rotary wing aircraft which can land nearly anywhere either powered or by autorotation. It is more difficult for a damaged fixed wing aircraft to successfully execute a forced landing (and/or subsequent takeoff) since some prepared landing site is generally required.

d. Mission Available Kill

This category covers those aircraft that have landed with combat damage and will require repair before returning to mission ready status. There are different levels (intervals) for mission availability. The interval of time required to accomplish repairs is expressed in elapsed time, total man-hours, cr combinations thereof.

2. Aircraft Description

At the beginning of any vulnerability study, as much as pcssible of the aircraft's technical and functional description must be gathered on each of the major systems of the aircraft. The aircraft's technical description ccnsists of engineering data which documents the physical and functional relationships of the aircraft's subsystems. The types of physical descriptions utilized are general aircraft arrangement drawings such as three view and inboard

37

profiles, installaticn drawings, and schematic diagrams for
the primary subsystems to include: airframe structure,
propulsicn system, fuel system, flight control system,
pneumo-hydraulic system, aircrew, avionics system, and
weapon and delivery systems. The suitability and quantity
of data available to produce the necessary aircraft
descriptions are functions of the status of the system
within the acquisiticn or deployment phase. Aircraft tech-
nical descriptions should utilize all of the data base to
include: engineering scaled drawings, subsystem functional
descriptions, technical orders and manuals, and access to
design personnel.

3. Critical Component Analysis

A critical ccmponent is any component that is essen-
tial to the functioning of a system, and if the compcnent
performance is sufficiently degraded or if the compcnert is
rendered inoperative by combat damage, a target kill in scme
kill category will result. Fcr example, the engine in a
single engine aircraft is a critical component for an A kill
because its loss would lead to an aircraft loss within five
minutes.

When two or more aircraft components are redundant,
such as two engines, the loss of any one of the redundant
components will not result in the loss of an essential func-
tion and hence, that component is not a critical ccmponent
according to the definition given above. This assumes that
the damage process and loss of one redundant component will
not lead to the loss cf any other redundant components. For
example, if one engine of a twin engine aircraft starts to
turn, the assumption is made that the fire will not spread
to the other engine and destroy it. If this were to happen,
there is no actual redundancy ard both engines are ncnredun-
dant critical components. Since more than one hit can be

38

expected in a typical threat encounter, it is possible that
all of the redundant components could be killed, leading to
an aircraft kill. Therefore, the fact that a component is
redundant does not eliminate it as a critical component.
This requires that a distinction between the two kinds of
critical components be made. In the past, nonredundant and
redundant critical components have been referred to as
singly vulnerable components and multiply vulnerable compo-
nents, respectively. This terminology is confusing and will
not be used here. A given component may be nonredundant
with respect to a given kill category and redundant with
respect to another kill category. For example, consider a
twin engine helicopter. If the loss of either engine causes
a mission abort, the engines are nonredundant for the
mission abort category. If the loss of both engines is
required to cause a crash or forced landing, the engines are
redundant for these two kill categories.

The first step in a critical component analysis is
to identify the flight and mission essential functions that
the aircraft must perform in order to accomplish its
mission. The second step is the identification of the major
systems and subsystems that perform these essential func-
tions. The third step is to conduct a Failure Mode and
Effects Analysis (FMEA) to identify the relationships
between each possible type of individual component or
subsystem failure mode and the performance of the essential
functions. The Fault Tree Analysis (FTA) 's sometimes used
to provide additional insight into the identification of
critical components. The fourth step is to conduct a Damage
Modes and Effects Analysis (DMEA). The DMEA relates compo-
nent or subsystem failure modes to combat-caused damage.
The combination of the third and fourth steps is referred to
as the Failure Mode, Effects, and Criticality Analysis
(FMECA). The last step in a critical component analysis is

39

Foreign Object Ingestion. Foreign objects
consist of projectiles, fragments, a ' pieces of damaged
aircraft components which enter the engine inlet and subseq-
uently damage the fan and compressor blades. This could
cause an engine failure or the throwing of blades through
the engine case, leading to additional component damage.

Inlet Flow Distortion. Distortion of air
flow to the engine can be so severe as a result of combat
damage to the inlet that uncontrollable engine surging or
engine failure occurs.

Lubrication Starvation. Penetrator, frag-
ment, or fire damage to the lubrication circulation and
cooling subsystem can result in loss of lubrication and
subsequent deterioration of bearing surfaces, followed by
engine inoperability. Loss of lubrication failures are most
often related to the bearings, where loss of heat removal
eventually results in bearing seizure.

Compressor Case Perforation or Distortion.
This kill mode is caused by penetrator or fragment penetra-
tion through the case, by distortion of the case, or by
damaged compressor blades exiting through the case.

Combustor Case Perforation. Penetrator or
fragment penetration and holing of the combustor case, with
subsequent hot gas emission or torching through the hole,
can cause secondary damage effects, such as severe heating
of adjacent fuel tanks or control rods, and can also cause a
combustion pressure drop that may result in a significant
loss of engine power.

Turbine Section Failure. Turbine failure
can be caused by penetrator or fragment damage to the
turbine wheels, blades, and case. This results in a loss of
engine power or secondary perforation and possible fire
damage.

subsequently ignited by incendiary particles, by hot metal surfaces, or by the hot gases from punctured bleed air lines or engine cases. Fire or explosion in the enclosed spaces can eventually cause significant damage to nearby subsystem components and structure that would result in their failure. The generation of smoke and toxic fumes may also occur and migrate to crew stations, causing a possible mission abort, forced landing, or aircraft abandonment.

Sustained Exterior Fuel Fire. This kill mode is caused by damage to fuel tank walls resulting in fuel spillage onto the exterior of the aircraft which is subsequently ignited, producing a sustained fire. Sometimes the exterior fire is snuffed out by the airflow over the surface; however, the condition of the damaged surface, the altitude, and the flight speed may prevent this from occuring.

Hydraulic Ram. Damage to container walls or components within the container caused by the intense pressure waves generated in the contained liquid by penetrators or fragments passing through the liquid is referred to as hydraulic ram damage. The fluid pressure can cause large cracks and gaping holes in the container walls, leading to excessive leakage either externally or internally into dry bays, engine inlets, etc..

(2) Propulsion System Kill Modes. The following kill modes of the propulsion system have been observed.

Fuel Ingestion. Fuel ingestion is caused by fuel entering the engine air inlet following rupture of walls that are common to both a fuel tank and the inlet. Fuel ingestion effects normally include compressor surge, severe stall, unstable burning in the tail pipe, and/or engine flameout.

TABLE 1

System Damage-Caused Failure Modes

Fuel
- Fuel Supply Depletion
- In-Tank Fire/Explosion
- Void Space Fire/Explosion
- Sustained Exterior Fire
- Hydraulic Ram

Power Train and Rotor Blade/Propeller
- Loss of Lubrication
- Mechanical/Structural Damage

Electrical Power
- Severing or Grounding
- Mechanical Failure
- Overheating

Propulsion
- Fuel Ingestion
- Foreign Object Ingestion
- Inlet Flow Distortion
- Lubrication Starvation
- Compressor Case Perforation or Distortion
- Combustor Case Perforation
- Turbine Section Failure
- Exhaust Duct Failure
- Engine Control and Accessories Failure

Crew
- Injury, Incapacitation or Death

Armament
- Fire/Explosion

Flight Control
- Disruption of Signal Path
- Loss of Control Power
- Loss of Aircraft Motion Data
- Damage to Control Surfaces and Hinges
- Hydraulic Fluid Fire

Structural
- Structure Removal
- Pressure Overload
- Thermal Weakening
- Penetration

Avionics
- Penetration/Fragment Damage
- Fire/Explosion
- Radiation Damage

There are many different kinds of damage-caused failures or kill modes that can occur within each of the systems of an aircraft. Failure modes for an aircraft are the various ways in which the aircraft can fail to be maintained in the required mode of flight or fail to perform its mission. These failure modes are constituted by the loss of, or serious degradation of, structural integrity, power, flight control or mission required equipment, or lift. Failure modes are established for a given aircraft and mission with respect to preestablished minimum requirements for performance of the aircraft and are related to the critical components of the aircraft. Some of the most important ones are listed in Table 1 and described below. The order of the systems listed is indicative of their contribution to the total aircraft vulnerability.

(1) **Fuel System Kill Modes.** The following is a listing and brief description of the potential fuel system kill modes.

Fuel Supply Depletion. This kill mode is caused either by damage to fuel storage components that results in excessive leakage leading to a significant reduction in the amount of fuel available for aircraft operation, or by damage to fuel pumping and transfer systems that prevents fuel from reaching the engine(s).

In-Tank Fire and Explosion. Fire and explosion can be caused by the ignition of the fuel-air mixture in the ullage by incendiary particles or by a hot tank wall. The in-tank fire or explosion can cause substantial damage to the tankage and adjacent structure and components, and the fire may quickly spread to other parts of the aircraft.

Void Space Fire and Explosion. This can be caused by fuel leakage into void spaces or dry bays (adjacent to punctured fuel tanks and lines) that is

50

Figure 2.6   A Sample Disablement Diagram

AIRCRAFT
SYSTEM FLIGHT CONTROLS (MECHANICAL)
FMEA REF

COMPONENT NAME	COMPONENT NUMBER	DISABLEMENT DIAG NO	DAMAGE MODE	"KILL" CATEGORY NON REDUNDANT			"KILL" CATEGORY REDUNDANT			REMARKS	$P_{k/h}$ FUNC NO
				ATTRITION	MISSION ABORT	VERTICAL	ATTRITION	MISSION ABORT	VERTICAL		
STICK ASSEMBLY (GRIP)	3001	1	BREAK OR DISABLE		X					DEGRADED FLIGHT CONTROL	32
CAS SENSOR	3002	2	LOSS OF ELECTRICAL CONNECTIONS (LOSS OF CAS)		X		X			LOSS OF CAS PITCH AND ROLL CONTROL CONTROL THROUGH DEL.	32
			LOSS OF ELECTRICAL AND MECHANICAL LINKAGES	X	X					REVERSION TO MECH (IF DEL IS LOST) (DEL-DIRECT ELECTRICAL LINK)	
RUDDER PEDALS ARMS	3006 3007		BREAK OR DISABLE ONE ARM								32
SUPPORT	3008	3	BREAK OR DISABLE	.							32
FEEL SPRING SUPPORT	3301		SUPPORT, FEEL							NO ELECTRICAL	32
SPRING	3302		SPRING ASSY, OR	X	X					INPUTS TO	32
TRANSDUCER	3303		TRANSDUCER							RUDDERS	24

Figure 2.5   A Sample DMEA Matrix

48

d. Damage Mode and Effects Analysis (DMEA)

In the FMEA the cause of the component failure is not stipulated. The failure may or may not be related to combat damage. When specific component failures due to combat damage, such as mechanical damage to components caused by projectile or fragment penetration or damage caused by a fire or explosion, are identified and examined, the analysis is referred to as a DMEA. In the DMEA, the potential component or subsystem failures identified in the FMEA, as well as other possible damage-caused failures, are associated with the damage mechanisms and the damage processes. These failures are then evaluated to determine their relationship to the selected kill level. The quantification of the component kill criteria is also part of the DMEA, but this procedure is described in the vulnerability assessment presentation. The possibility of any secondary hazard that may be caused by the primary damage processes is also identified in the DMEA. Examples of secondary hazards are: ingestion of fuel by an engine, and seepage of toxic fumes from a fire into the cockpit. The DMEA is referred to as the criticality analysis of the FMECA.

The output of the DMEA can take many forms. The DMEA matrix is similar to the FMEA summary format shown in Figure 2.4 in which the components and their damage-caused failure modes are related to the kill level or category. Component redundancy relationships and the appropriate component kill criteria should also be indicated in the matrix. A sample DMEA matrix is given in Figure 2.5. A disablement diagram can add to the understanding of the DMEA matrix by graphically showing the locations of the components and stating the effects of component kills. A sample disablement diagram is presented in Figure 2.6.

47

AIRCRAFT SUBSYSTEM	SUBSYSTEM		FAILURE MODE	EFFECT ON SUBSYSTEM	EFFECT OF DEGRADED SUBSYSTEM ON AIRCRAFT	AIRCRAFT KILL CATEGORY	SUPPORTING REFERENCES	COMMENTS
	COMPONENT	LOCATION						
FLIGHT CONTROLS	ROD 3127	LEFT WING	SEVER	AILERON GOES TO HARDOVER (UP) POSITION	HARDOVER EFFECT CAN BE BALANCED WITH OTHER CONTROL SURFACES	AIRCRAFT CAN FLY AND LAND USING OTHER CONTROL SURFACES	#1	1, 2
			JAM	PILOT'S CONTROL STICK IS LOCKED	NO CONTROL OF FLIGHT	ATTRITION	#7	

Figure 2.4   Sample PMEA Summary Format

determination of the major structural or aerodynamic damage
tolerances is also performed during the FMEA. In addition,
the effects of loss or major damage to aerodynamic surfaces
on stability and control of the aircraft are required. Data
generated should define the threshold for aerodynamic,
structural, and control limits that can be tolerated for
various flight conditions. A sample summary format for a
FMEA for two flight control rod failure modes is given in
Figure 2.4. Note in Figure 2.4 that the control rod is a
critical component for an attrition kill when it jams, but
not when is is severed.

The FMEA is applicable to both single component
failures and multiple component failures. It is extremely
important to consider multiple component failures, when the
failure is due to combat damage, because of the likelihood
that more than one component is damaged when the aircraft is
hit.

The effects of a component failure should also
include the consideration of any transients that might occur
when the failure occurs. For example, consider a single
engine, fly-by-wire, statically unsTable aircraft with no
mechanical flight controls as back-up. Suppose the engine-
driven generator that supplies the electrical power to the
flight control computer was to immediately cease operation
and that the computer relies on an emergency ram-air turbine
(RAT) for back up electrical power. The RAT is designed to
be deployed into the airstream when the electrical power
failure is sensed. However, this deployment takes time,
during which the computer could be without sufficient power.
This lack of power could cause problems with the fly-by-wire
control system such as the loss of the SAS or the issuance
of hardover commands to the control surfaces which could
cause the aircraft to become uncontrollable, leading to an
aircraft loss. Thus, the assumption of redundancy in the
electrical power system is erroreous.

45

Subsystem function ID letter	SUBSYSTEMS FUNCTIONS	ESSENTIAL FUNCTIONS										
		Provide lift and thrust	Provide controlled flight	Communications	Start systems	Monitor systems	Provide air data intelligence	Maintain terrain clearance	Employ IFF/ECM	Navigate	Locate/identify targets	Employ weapons
a	Generate electrical power											
b	Provide automatic control and protection of power generation											
c	Distribute electrical power											
d	Provide automatic protection of power distribution											
e	Provide power conversion (dc and low-voltage ac)											
f	Provide battery power											
g	Control subsystem loads											
h	Process and transmit subsystem data and power control signals											
i	Provide automatic electrical load management											
j	Provide controls and displays											
k	Provide illumination											

**Figure 2.3   Subsystem Functions-
Essential Function Relationships**

The types of component failure modes generally
considered in the FMEA include premature operation, failure
to operate, failure during operation, failure to cease oper-
ation, and degraded or out-of-tolerance operation.   A

ITEM	ESSENTIAL FUNCTIONS	RELATED SYSTEMS									
		Electrical power	Hydraulic power	Flight control system	Propulsion system	Crew system	Fuel system	Power train/ rotor blade system	Avionics	Armament	Structure
	FLIGHT:										
1	Provide lift and thrust										
2	Provide controlled flight										
	MISSION:										
3	Communications										
4	Start systems										
5	Monitor systems										
6	Provide air data intelligence										
7	Maintain terrain clearance										
8	Employ IFF/ECM										
9	Navigate										
10	Locate/Identify targets										
11	Employ weapons										

Figure 2.2 System-Essential Function Relationships

43

ITEM	ESSENTIAL FUNCTIONS	MISSION PHASES							
		Alert	Takeoff	Cruise to laager area	Cruise to holding position	Cruise to assault position	Engage targets	Return cruise	Land
	FLIGHT:								
1	Provide lift and thrust								
2	Provide controlled flight								
	MISSION:								
3	Communications								
	• secured voice								
	• unsecured voice								
	• ICS								
4	Start systems								
5	Monitor systems								
6	Provide air data intelligence								
7	Maintain terrain clearance								
8	Employ IFF/ECM								
9	Navigate								
10	Locate/identify targets								
11	Employ weapons								

Figure 2.1   Some Essential Functions and Mission Phases
for an Attack Helicopter

42

These include special functions such as those required for the vertical flight cf a VTOL aircraft or those required for arrested landing aboard an aircraft carrier. A chart identifyirg some flight ard mission essential functions and scme of the mission phases for an attack helicopter is given in Figure 2.1.

b. System-Essential Furctions Relationships

The ability of an aircraft to fly and to conduct its mission depends upon the continued operaticn of those systems and subsystems that perform the essential functions. If the aircraft is damaged ir combat, the operaticn of certain subsystem components may be impaired or the compo- nent may cease to operate, and some essential functions may be lost. The severity and rapidity with which the lcss of essential functions cccur is directly related to the kill levels.

A general examinaticn of each aircraft's systems and subsystems must be conducted to determine its specific contributicn to the essential functions identified in the previous step. Figure 2.2 presents a sample tabulaticn of those systems and subsystems that contribute to the essen- tial functions shown in Figure 2.1. A more detailed example of the relationship between the functions performed by cne specific subsystem and the essential functions is shcwn in Figure 2.3.

c. Failure Mode and Effects Analysis (FMEA)

The Failure Mode and Effects Analysis is a procedure that: (1) identifies and documents all pcssible failure modes of a ccmponent or subsystem, and (2) deter- mines the effects of each failure mode upon the capability of the system and/cr subsystem to perform its essential functions. The FMEA frocess and requirements are defined in MIL-STD-785 and MIL-STD-1629A.

41

a visual presentation of the list of critical components and/or a logical expression to identify the redundant and nonredundant critical components for the selected kill level. The visual presentation is referred to as a kill tree and the logical expression is referred to as a kill expression.

a. Flight and Mission Essential Functions

Flight essential functions are those system and subsystem functions required to enable an aircraft to sustain controlled flight. Mission essential functions are those system and subsystem functions required to enable an aircraft to perform its designated mission. The analysis should consider each phase of the mission. A typical mission for an attack aircraft would include such phases as takeoff, climb to cruise altitude, cruise to attack area, descent to attack altitude, target location, ordnance delivery, egress from the target area, climb to cruise altitude, return cruise, descent, and landing. The flight and mission essential functions should be identified and the priority for possible protection established for each of these phases. For example, the operation of the electronic weapons computer during takeoff is not a flight essential function, but it is a mission essential function during ordnance delivery. A particular level of operation should be identified for the flight essential functions such as lift, thrust, and control. For example, loss of one engine of a twin engine helicopter may not cause a total loss of lift and thrust, but it will lead to a reduction of performance capabilities. This loss of performance may not be acceptable in a hostile environment because the helicopter would become an easy target. Therefore, the continued operation of both engines may be required to prevent an attrition kill. Special functions must also be identified.

Exhaust Duct Failure. Penetration by
penetrators and fragments into the exhaust duct may result
in damage to nozzle control lines and actuator mechanisms
and possible fuel spillage and secondary fire if an
augmentor is operating at the time of the hit.

Engine Controls and Accessories Failure.
A kill of the controls and accessories can be caused by
penetrator, fragment, or fire damage. The result can be
loss of control of the engine or loss of one of the impor-
tant accessories.

(3) Flight Control System Kill Modes. Some
possible flight control kill modes are listed below.

Disruption of Control Signal Path.
Severence or jamming of the mechanical or electrical path
that transmits the control signals from the pilot to the
control surfaces or the actuators can partially or totally
incapacitate the control system.

Loss of Control Power. Control power can
be lost as a result of damage to hydraulic power components
which causes a loss of hydraulic pressure. Types of power
system damage are thermal degradation due to fire, perfora-
tion of hydraulic reservoirs, cylinders, or lines leading to
a loss of hydraulic fluid, and deformation of hydraulic
components, actuators, or lines that cause a hydraulic lock
or jammed condition.

Loss of Aircraft Motion Data. Damage to
the aircraft motion sensors or to the sensor data signal
paths to the flight control computer can prevent the auto-
pilot and the stability augmentation system from properly
controlling the motion of the aircraft. The results can
vary from a partial loss of control, leading to a mission
abort, to the loss of an out-of-control aircraft. These
components are relatively soft and are easily damaged or
severed by penetrators, fragments, and fire.

54

Damage to Control Surfaces and Hinges.
Penetrators, fragments, blast, and fire damage can result in
the physical removal of a portion or all of a flight control
surface or in the jamming of the hinges, rods, and other
linkages between the servoactuators and the control
surfaces.

Hydraulic Fluid Fire. Fires can result
from the ignition of pressurized or gravity-leaked hydraulic
fluid, and smoke or toxic fumes from the fire can affect the
crew.

(4) Power Train and Rotor Blade/Propeller
System Kill Modes. Some of the possible kill
modes within the power train and rotor blade system of heli-
copters and propeller driven fixed-wing aircraft are
described below.

Loss of Lubrication. This kill mode can
occur due to projectile or fragment perforation of oil or
grease containing components, with subsequent loss of lubri-
cation oil or grease. Lubrication starvation is especially
critical in oil-cooled helicopter transmissions, where the
oil systems are not self-contained and usually consist of
externally mounted components, such as sumps, filters,
coolers, and interconnecting lines and hoses. Loss of
lubrication prevents the removal of heat and lubrication of
rubbing surfaces, which eventually results in component
seizure. In helicopter transmissions and gear boxes, fail-
ures are often catastrophic, causing case rupture and fire
after input pinion failures and rotor blade seizure after
planetary assembly failures.

Mechanical/Structural Damage. Mechanical
or structural failure of power train components can be
caused by fragment and penetrator impact or penetration, or
by fire. Bearings, gears, and shafts are prone to damage
and failure when hit, shafts can be severed, and bearings

55

and gears can jam. Chips and debris from damaged components or structure can jam the oil pump, causing loss of lubrication. Rotor blades and propellers when hit can result in rotor unbalance, blade instability, blade out-of-track, and loss of lift. Rotor unbalance is perhaps the most critical consequence of ballistic damage and occurs when a portion of the blade is removed. This loss of mass in one blade can cause large, alternating hub forces and intense cockpit and control vibrations, leading to structural failure or loss of control. Blade instability is caused by a reduction of blade stiffness due to damage and can result in severe flutter or divergent pitch oscillation that can be catastrophic. Blade out-of-track is usually a less severe result of the reduction of blade stiffness, but it could result in blade contact with the fuselage. Although some loss of lift normally accompanies any ballistic damage, the consequences are usually not as catastrophic as those associated with the other types of blade reactions.

(5) Crew System Kill Modes. The inability of the pilot and his or her replacement to operate the aircraft because of injury, incapacitation, or death will usually lead to an aircraft kill in a very short period of time.

(6) Structural System Kill Modes. The structural system is usually the toughest system on the aircraft. However, structural damage can be sufficient to cause an aircraft kill. Some possible structural kill modes are listed below.

Structure Removal. Physical severence or complete loss of large portions of the load-carrying aircraft structure caused by multiple penetrators and fragments, blast, fire, or radiation effects can result in either an immediate or a delayed aircraft loss.

Pressure Overload. Immediate failure or subsequent failure under maneuver loads can be caused by

external blast effects which result in over-stressing the load carrying structure.

Thermal Weakening. Structural failure can occur to portions of the load-carrying structure as a result of internal void space fires, externally sustained fires, or radiation over a portion of the aircraft surface.

Penetration. A single penetration of one load-carrying member will usually not cause structural failure; several members must be penetrated or cut before failure can occur. Since the likelihood of structural failure from penetration by a few fragments or armor-piercing projectiles is extremely small, this type of failure would most likely result from continuous rod warhead effects.

(7) Electrical Power System Kill Modes. The failure of electrical system components is due to the severing or grounding of electrical circuits, the destruction or unbalancing of rotating components, such as generators and alternators, and the penetration or overheating of batteries.

(8) Armament System Kill Modes. Two major reactions can occur when gun ammunition, bombs, rockets, and missiles are hit by a damage mechanism. One is a sustained fire in the magazine that could cause cook-off or detonation of the stored ammunition, and the other is a severe explosion of either the armament or the propellant.

(9) Avionics System Kill Modes. Avionics components are usually very soft and are easily damaged by penetrators and fragments, blast, radiation, and thermal hazards, such as fire or hot gas torching. Their kill mode is usually failure to operate, although a degraded operation is possible.

e. Fault Tree Analysis (FTA)

As described in the preceding section, the FMEA
is a bottom-up approach to determine an aircraft's critical
components. In the FMEA, the failure of a component is
assumed and the consequences of that failure are identified.
Another procedure for identifying critical components is the
Fault Tree Analysis. The FTA is a top-down approach which
starts with an undesired event and then determines what
event or combination of events can cause the undesired
event. The Fault Tree Analysis is one of the principal
methods of system safety analysis, and can include both
hardware failures and human effects. The generic fault tree
diagram shown in Figure 2.7 demonstrates the logic symbology
used in the Fault Tree Analysis.

The undesired event U can only occur when event
A and event B occurs. (This is the logical AND gate). Event
A can occur when event C or event D occurs, or if both event
C and event D occurs. (This is the inclusive OR gate).
Event B can occur when event E or event F occurs, but not
when both event E and event F occurs. (This is the exclusive
OR gate). Because the undesired events of interest here are
failures caused by damage, the FTA will be referred to as
the Damage Tree Analysis.

A portion of a damage tree diagram for a twin-
engine aircraft with a single fuel supply source to both
engines is illustrated in Figure 2.8c. The undesired event
is an aircraft attrition kill. An attrition kill occurs if
the aircraft can neither fly nor land. The aircraft cannot
fly if it loses lift, or thrust, or control. Loss of thrust
will occur when both engines fail or when the common fuel
supply to both engines fails. Leakage from damage caused by
penetration or hydraulic ram from the feed tank that
supplies fuel to both engines will cause the fuel system to

58

Figure 2.7   A Generic Fault Tree Diagram

fail.   The left engine can fail due to engine damage or the
loss of the left engine fuel supply.   The left engine fuel
supply system can fail due to penetration of many of the
fuel transfer components from the feed tanks to the engine
combustor, or these components can fail due to fire caused
by leaking fuel, leaking hydraulic fluid, or a holed combu-
stor. The left engine can fail due to damage caused by fuel
ingestion, penetration of the engine compressor, combustor,

or turbine, loss of lubrication, fire caused by leaking fuel, or damage to the engine controls or accessories.

f. Kill Trees and Kill Expressions

Results of the steps described above leads to the identification of a set of critical components in a particular aircraft design, for a specific operational mode

Figure 2.8a   Portion of a Damage Tree Diagram
for a Twin Engine Aircraft

Figure 2.8b   Portion of a Damage Tree Diagram Cont'd

Figure 2.8c   Portion of a Damage Tree Diagram Cont'd

and selected kill level.   Each critical component either
makes a singular contribution to an essential function or
each component is one of two or more redundant components,
each cf which can make the necessary contribution.   The
distinction between nonredundant critical components and
redundant critical components is extremely important and
will be demonstrated in the following sections.

(1) Typical Critical Components. For a two engine, single pilot helicopter, the following nonredundant components are potential critical components for an attrition kill: (1) Flight control system components (rods, rod ends, bellcranks, pitch links, swashplate, hydraulic actuators, collective lever, and control pedals), (2) Rotor blade and power train components (blades, drive shafts, rotor heads, main transmission, and gear boxes), (3) Fuel system components (fuel cells, the sump, lines, and valves), (4) Pilot, and (5) Tail boom.

The following redundant components are potential critical components for an attrition kill: (1) Propulsion system components (engine and engine mounts), (2) Hydraulic subsystem components, and (3) Structural elements.

For a single engine, single pilot, fixed-wing aircraft, some potential redundant and nonredundant critical components are: (1) Pilot, (2) Flight controls in the cockpit and the pitch axis flight control components, (3) Hydraulic reservoirs, high-pressure lines, components and actuators, (4) All fuel tanks, components, lines, and shut-off valves, (5) Engine fan, compressor, turbine, and combustor sections, drive shaft and bearings, engine mounts, and the lubrication and fuel supply components, (6) Major structure, such as wing box spars, fuselage longerons, and the horizontal and vertical stabilizer spars and attachments, (7) External ordnance and the ammunition storage drum, (8) Liquid oxygen (LOX) bottle and components, and (9) Liquid-cooled avionics with a flammable coolant.

(2) The Kill Tree. A visual illustration of the critical components and of the contribution of component redundancy is provided by the kill tree. In order to kill the aircraft a complete cut through the tree trunk is required. A sample kill tree for a two engine, two pilot

63

helicopter is shown in Figure 2.9. For example, according
to the kill tree in Figure 2.9, a loss of the pilot and
either the co-pilot or the co-pilot's controls will lead to
an aircraft kill, as will a loss of the drive train or loss
of fuel feed.

(3) The Kill Expression. The relationship
between component loss and an aircraft kill can be expressed
using the logical AND and OR statements. This logical
expression is called the kill expression. As an example, a
portion of the kill expression for the kill tree depicted in
Figure 2.9 is given by:

[(Pilot .OR. Pilot Controls) .AND. (Copilot
.OR. Copilot Controls)] .OR. (Engine 1 .AND.
.OR. (Drive Train) .CR. etc.

C. VULNERABILITY ASSESSMENT

1. Defining a Vulnerability Assessment

A vulnerability assessment is the process of deter-
mining numerical values for the measures of vulnerability.
Target vulnerability analysis is a scientific discipline
involving both experimental and analytical processes.
Preliminary theories which attempt to describe the response
of a target to a particular threat is accomplished during
the analysis.   Experimentation provides the data used to
corroborate or repudiate the theories developed during anal-
ysis.   Target vulnerability concepts are based on funda-
mental physical principles. These principles include the
theory of: hydraulic ram, ignition, crack propagation,
engine response to fuel ingestion, and structural response
to blast and penetration. Vulnerability assessments may be
carried out entirely "by hand", or one or more computer
programs may be used. Assessments are usually conducted to
help the designer evaluate the vulnerability of a design, or

64

Figure 2.9 Sample Kill Tree for a Two
Engine Two Pilot Helicopter

65

more importantly, by the military to predict the response of targets to a particular threat before threat and target engagement.

A vulnerability assessment is carried out at one of three general levels cf detail. These levels are estimates, evaluaticns, and analyses. Most assessments consider five fragment impact velccities frcm 1000 to 10,000 ft/sec and use as a minimum, the six cardinal aspects. For a minimum level assessment, the six major aspects shown in Figure 2.10 are usually considered for each kill level. The 26 aspects depicted in Figure 2.11 are usually considered when a more detailed analysis cr a computer analysis is perfcrmed. Estimates typically use simple equations for the aircraft vulnerability measures that are functions of a few major parameters. These equations are referred to as regression equations if they are fitted tc historical data on several aircraft or to the results from enjineering studies. Evaluations are more detailed than estimates and may include such items as the individual ccmponent locations, sizes, and vulnerability measures. Analyses are very detailed assessment studies that use specific technical and functioral information about the components and their vulnerability. Analyses are usually conducted on a ligital computer using complex gecmetric target models.

2. Vulnerability Measures

Because of the diverse nature of the hostile environment in which aircraft operate, the measures of the vulnerability of an aircraft vary with the type of threat encountered. For example, if a hit on the aircraft must cccur in crder for a threat to be effective, such as a small arms projectile and a contact-fuzed high explosive warhead, one measure of vulnerability is the conditional probability the aircraft is killed given a random hit on the aircraft,

66

Figure 2.10   Six Aircraft Aspects for a Minimum Assessment

The numerical value for P_{k/H_i} depends upcr the presented area of the critical component, A_{p_i}, and of the aircraft, A_p, and upon the compcnent kill criterion, P_{k/h_i}. The presented area cf the critical components and of the aircraft can be obtained frcm the available techrical description of the aircraft. The procedure for determining the numerical value for P_{k/h_i} is described in the presentation cn the critical component kill criteria given akove.

In this assessment, a component is assumed to be either operating and performing all of its functions or killed. No degradaticn of compcnent capabilities is ccnsidered due to a hit, and no compounding of component damage is recognized. Althougk these assumptions are usually made in a vulnerability assessment, they are not necessary. Theoretically, only the comfonent hit can be killed. Although the kill of adjacent ccmponents, perhaps by fire or explosicn, is not directly considered here, a procedure for indirectly accounting for kills of adjacent components will te described later.

Now that the concepts of vulnerable area and the probability of kill given a hit have been explained, the scenario must be corsidered. In any given combat engagement, the aircraft will either not be hit, it will te hit only cnce, or the aircraft will be hit more than once. The ro hit situation is not of interest here. The locaticn cn the presented area of the aircraft of the single hit ard of multiple hits is assumed in the vulnerability assessment to te a randcm distribution, with each damage mechanism having the same approach or attack direction. In cther words, the assumpticn is usually made that the enemy has no capability to direct hits to any one particular component, subsystem, cr part of the aircraft, and that the damage mechanisms travel along parallel shotlines. The single hit case lays the grcund work for the multiple hit case. In both cases,

81

Since both A_{p_i} and P_{k/h_i} are generally functions of the threat direction or aspect, the vulnerable area will also vary with aspect. In the discussion that follows, it is important to recall that:

$$P_{S/H} = 1 - P_{K/H} \qquad (2.2)$$

where $P_{S/H}$ is the probability the aircraft or component survives the hit, and $P_{K/H}$ is the probability of killing that aircraft or component.

The kill probability of the ith component given a random hit on the aircraft, P_{k/H_i}, is:

$$P_{k/H_i} = P_{h/H_i} \times P_{k/h_i} \qquad (2.3)$$

where P_{h/H_i} is the probability the component is hit given a hit on the aircraft, and P_{k/h_i} is defined as the probability the component is killed given a hit on the component. From Equation 2.2, it follows that:

$$P_{S/H_i} = 1 - P_{k/H_i} \qquad (2.4)$$

Using Equations 2.1 and 2.3, and solving for P_{h/H_i} gives:

$$P_{h/H_i} = A_{p_i} / A_p \qquad (2.5)$$

where A_p is the presented area of the total aircraft in the plane normal to the threat direction. Substituting Equations 2.5 and 2.1 into Equation 2.3 determines, for any random hit on the aircraft, the probability the ith component is killed, and is given by:

$$P_{k/H_i} = A_{v_i} / A_p \qquad (2.6)$$

80

its critical components. The vulnerable area of the typical ith component is denoted by A_{v_i}, and the component kill criterion used is the probability of kill given a hit, P_{k/h_i}. To assist the reader in keeping track of the notation used in this presentation, the variable and subscript definitions are summarized in Table 2.

TABLE 2
Vulnerability Assessment Variable Definitions

Definition	Variable
Probability of killing the ith component given a hit on the ith component	P_{k/h_i}
Probability of killing the ith component given a hit on the aircraft	P_{k/H_i}
Probability of killing the aircraft given a hit on the aircraft	$P_{K/H}$
Vulnerable area of the ith component	A_{v_i}
Vulnerable area of the aircraft	A_V
Presented area of the ith component	A_{p_i}
Presented area of the aircraft	A_P

Note that a distinction is made between component and aircraft designated variables by using lower and upper case subscripts, respectively.

The vulnerable area of the ith component is defined as the product of the presented area of the component in the plane normal to the approach direction of the damage mechanism (the shotline), A_{p_i}, and the probability of kill of the component given a hit on the component, P_{k/h_i}. Thus,

$$A_{v_i} = A_{p_i} \times P_{k/h_i} \qquad (2.1)$$

79

Figure 2.14   Typical Aircraft Encounter With
An Externally Detonating BE Warhead

C. VULNERABILITY TO EXTERNALLY DETONATING WARHEADS

Vulnerability of an aircraft to an externally detonating high explosive warhead is usually analyzed in two steps. The first step is a determination of the aircraft's vulnerability to the blast, and the second step analyzes the aircraft's vulnerability to the fragments and penetrators. In addition, both analyses must consider the encounter scenario between the aircraft and the missile at the time of warhead detonation. For this reason, this section has been divided into the following two subsections: the effect of fragments and penetrators striking an aircraft, and blast. Shortly after detonation, the blast front precedes the fragments. Eventually, the fragments pass through the blast front because the fragment velocity decay is less than the blast front velocity decay. The overpressure caused by the warhead detonation can cause serious damage to aircraft structure and components. Using the conditions of the encounter scenario, the blast is analyzed for impulse and overpressure to determine iso-damage contours for an aircraft kill. If a detonation occurs close enough to inflict serious blast damage, the fragments most likely will cause much more damage than that caused by the blast. In the fragments and penetrators subsection, the vulnerability to fragments and penetrators is computed for both the single hit case and the multiple hit case. A typical encounter is shown in Figure 2.14.

1. Effect of Fragments/Penetrators Striking an Aircraft

The vulnerability of an aircraft to a single impacting penetrator or fragment is usually expressed as a total vulnerable area, A_V, or as a probability of aircraft kill given a random hit on the aircraft, $P_{K/H}$. The vulnerable area concept is applicable to both the aircraft and to

77

(2) Energy Density. In this criterion, a component kill is expressed in terms of a required minimum component surface area that must be exposed to a minimum threshold level of the kinetic energy density of the impacting damage mechanisms. This criterion is applicable to closely spaced multiple fragment hits and is used for the structural components, as well as other large components, such as the fuel tanks and engines. For some components, there may be a minimum mass of the damage mechanism below which the criterion is not applied.

(3) Blast. The damage criterion for blast is generally the critical values of pressure and impulse on an aircraft surface necessary to cause the specific component damage level associated with the assumed kill level. For example, a dynamic overpressure of two pounds per square inch over the upper surface of a horizontal tail for one millisecond may be sufficient to cause crushing of the skin, leading to a loss of stiffness and the inability to support the flight loads. Although this criterion is usually applied to the structural components and control surfaces, the effects of the blast can extend into the interior of the aircraft and can damage electrical wiring, hydraulic lines, fuel tank walls, and other internal components located close to the aircraft skin.

c. Computation of the Vulnerability Measures

The procedures used to compute the vulnerability of an aircraft and its components to an externally detonating high explosive warhead and non-explosive penetrators or fragments, to an internally detonating high explosive warhead, and to lasers are described in the following three sections.

76

limited gunfire testing provides some insight into the effects of projectile and fragment damage potential, there is no universal methodology for arriving at a numerical value for $P_{k/h}$. The larger components, such as the fuel tanks and engines, are especially difficult to evaluate due to the multitude of local environments, the constantly changing operation conditions, and the many different failure modes. Numbers for $P_{k/h}$ are eventually assigned based upon a combination of empirical information, engineering judgment, and experience.

The location of the component inside the aircraft will have an influence on its ultimate numerical probability of kill given a hit, but not on its $P_{k/h}$ function. Components located behind thick structures or dense equipment packs will receive a level of protection due to the slowdown of the damage mechanism as it attempts to penetrate the shielding components. The numerical value of the $P_{k/h}$ for the lowered velocity of impact will generally be less than the $P_{k/h}$ for the impact of a penetrator or fragment that was not slowed down. Other considerations, such as spall and fragment breakup caused by the intervening components also becomes important.

The area removal criterion defines a specific amount of area that must be removed from a component in order to kill that component. This criterion is applicable to large penetrators, such as rods, and to the closely spaced hits from many fragments. The total component damage from a collection of closely spaced hits can be greater than the sum of the individual damages from the same number of widely spaced hits. Often there is a synergism of damage due to cracking and petalling between the individual holes, and large areas of component structure can be removed or destroyed. This criterion is used mainly for structural components.

Figure 2.13 Engine $P_{k/h}$ Data

engine could be subdivided into the major sections illustrated in Figure 2.13.

The determination of the $P_{k/h}$ for each component or part of a component is a very difficult undertaking. It requires a combination of critical component analysis data and sound engineering judgment. Although

Figure 2.12   Typical $P_{k/h}$ Data for a Flight Control Rod

73

or penetrator striking velocity, obliquity angle, shape and mass of the fragment or penetrator, to be estimated for each kill category and level being assessed. In the case of externally detonating warheads, high explosive projectiles, and contact-fuzed missiles, miss distance boundaries relating $P_{K/H}$ to burst points are established to assess blast effects of these threats.

The major result of this task is the specification of numerical values for the kill criteria for each failure mode for each critical component for each threat to be considered. Three specific kill criteria are currently in use for the impacting damage mechanisms. They are the probability of component kill given a hit, the area removal criterion, and the energy density criterion. There is a fourth criterion which applies to the blast damage mechanisms.

(1) The Probability of Kill Given a Hit Function. The $P_{k/h}$ function defines the probability of a component kill when impacted by a fragment or penetrator. This criterion can be presented graphically as a function of the mass and velocity of the damage mechanism, or it can be expressed in an analytical form. Figure 2.12 is a sample of $P_{k/h}$ data for a flight control rod.

The $P_{k/h}$ criterion is normally used for components that can be killed by a single hit, such as crew members, control rods, electronic equipment, and servoactuators. These components are sometimes referred to as single fragment vulnerable components. It can also be used for some of the larger components, such as engines and fuel tanks. In this case, the volume of the large component is usually divided into several smaller volumes, and a different numerical value of $P_{k/h}$ is assigned to each volume. For example, a fuel tank could be divided into the ullage, fuel, and external void spaces, and a turbojet

72

within the aircraft. This high explosive detonation produces internal blast and fragmentation effects. These fragments usually are smaller and slower than the larger high explosive projectiles but the proximity of the detonation to the critical components results in a spray of many fragments impacting the components. This combination of internal blast and fragmentation effects is especially lethal to lightly constructed components such as oil and fuel lines, oil and fuel tanks, hydraulic tanks, and the aircrew.

b. Critical Component Kill Criteria

Once the set of critical components for a given aircraft has been identified, the damage or kill criteria for each of the failure modes of these components must be determined for the selected threats. Damage criteria for a critical component is the level of damage required for a preestablished degradation of the performance of the component. Thus, a kill criterion is the specific descriptive characteristics or quantification of a component failure. Some examples of critical component kill criteria are: the amount of material that must be removed from a drive shaft for failure, requirements for failure of a structural member, the amount of damage required to incapacitate a system of gears, the minimum diameter of hole in a fuel tank or line for engine starvation within a specified time period, etc. Very few kill criteria are precisely known, nor can they easily be determined. Battle damage reports are an important source of component damage effects information. The results of tests conducted on all types of aircraft components and subsystems provide another increasingly important and expanding source of data. Data is required for each critical component that allows for the effects of encounter parameter variations, such as fragment

71

a. Threat Selection

Because of the many diverse and terminal effects
of the various damage mechanisms, each vulnerability assess-
ment is usually made considering either a specific threat or
a specific damage mechanism. Mechanisms which may cause
damage to an aircraft may be classified as: kinetic energy
penetrators such as projectiles and fragments, internal and
external blast, pyrophorics, shaped charged jets, focused
blast fragments and lasers.

Kinetic energy penetrators include, but are not
limited to, ball projectiles, armor piercing projectiles,
and fragments. These penetrators cause damage to aircraft
components during penetration and perforation. Armor
piercing projectiles are constructed with a hardened core
which enhances the penetration characteristics of these
projectiles over those of the ball type. Most small armor
piercing projectiles are prone to tumbling after impact
thereby increasing the size of the hole that they tear in
the internal components.

Armor piercing incendiary projectiles contain an
incendiary mix encased within the nose of the projectile
ahead of a hardened case. Upon impact the jacket peels off,
and the incendiary material flashes as the projectile core
penetrates the target.

Large high explosive projectiles and missiles
can be equipped with influence or command fuzes causing them
to detonate nearby an aircraft. These projectiles or
missiles have the capability of inflicting damage from
external blast effects, fragment impact effects, or a combi-
nation of both.

Many smaller high explosive projectiles are
equipped with delay fuzes. These fuzes initiate upon
contact with the aircraft skin and detonate the projectile

70

$P_{K/H}$.   Another measure of vulnerability to impacting damage mechanisms is the aircraft's vulnerable area, A_v . Vulnerable area is a theoretical, non-unique area presented to the threat which, if hit by a damage mechanism, would result in an aircraft kill.   Cr the other hand, when damage is caused by the effects of a rearby high explosive detonation, the vulnerability may be expressed in the fcrm of a $P_{K/D}$ (probability of kill given a detonation) envelope. This envelope represents a kill probability contour about the aircraft on which a specified detonation will result in a certain probability of aircraft kill.   If only the blast from the exploding warhead is considered, the env⁻lcpe represents the aircraft's vulnerability to external b ist. A measurement which is becoming more important relates to aircraft vulnerability to a laser threat.   Laser vulnerability can be measured by the probability of kill, given a specific power laser lock-on for a specified period of time, $P_{K/Lo}$.

3.   General Requirements

Certain required elements of a vulnerability assessment are common to all studies, regardless of the type of threat considered.   These elements are: (1) a selection of the aircraft kill levels or categories to be assessed,   (2) an assembly of the technical and functional descriptions of the aircraft, (3) a determination of the critical components of the aircraft, (4) a selection of the specific threats the system will encounter, (5) an analysis to identify the type and amount of damage required to kill each critical component, and (6) the computation of the appropriate vulnerability measures for the components and the aircraft based upon the threat selected.   The first three steps of the assessment have been described in the preceding section.   A presentation of the last three steps follows.

Figure 2.11   26 Aircraft Aspects for a Detailed Analysis

the influence of nonredundancy and redundancy of components
on the vulnerable area must be examined. Overlap of crit-
ical components is also an important consideration.

a. Single Hit Vulnerability

Both the nonredundant aircraft model and the
redundant aircraft model considered in this section are
assumed to receive only one hit. The nonredundant aircraft
model is composed of only one of each of the critical compo-
nents. Thus, the loss of any one critical component will
cause the loss of the aircraft. In the redundant aircraft
model, some of the critical component functions are dupli-
cated by the same or different components. The effects of
overlapping of both nonredundant and redundant critical
components are examined. For example, the fact that an
engine overlaps (shields) a hydraulic pump will probably
decrease the probability of kill of that pump. It is neces-
sary to specify how this overlap effect is quantified for
both the nonredundant and redundant aircraft models.

(1) Aircraft Model Composed of Nonredundant
Components with No Overlap. This aircraft
consists of N critical components whose functions are not
duplicated by any other component. The components are
arranged in such a way that no components overlap when
viewed from a given aspect. Any hit on the aircraft takes
place along a shotline that passes completely through the
aircraft. Thus, no more than one component can be hit on
any one shotline. As an example, Figure 2.15 shows an
aircraft consisting of three critical components: a pilot,
one fuel tank, and one engine. None of the critical compo-
nents overlap in the aspect presented in Figure 2.15.

The probability of killing this aircraft,
given a random hit on the presented area in Figure 2.15, can
be derived using the kill expression and Equations 2.1 and

82

Figure 2.15   Nonredundant Aircraft Model With No Overlap

2.6. For an aircraft composed of N nonredundant critical components, the kill expression is:

$$Kill = (Nrc1) \ .OR. \ (Nrc2) \ .OR. \ ... \ (NrcN) \qquad (2.7)$$

where $Nrci$ refers to a kill of the ith nonredundant component. In other words the aircraft kill is defined by the kill of nonredundant component number 1, or nonredundant component number 2, or ..., or nonredundant component number N. Because a kill of any one of the critical components will kill the aircraft, the aircraft will survive only if all of the nonredundant critical components survive. Thus,

$$P_{S/H} = P_{s/H_1} \times P_{s/H_2} \times ... \times P_{s/H_N} \qquad (2.8)$$

Using Equation 2.4, Equation 2.8 may be written as:

$$P_{S/H} = (1 - P_{k/H_1}) \times (1 - P_{k/H_2}) \times \qquad (2.9)$$
$$... \times (1 - P_{k/H_N})$$

For our model aircraft N=3, and Equation 2.9 becomes:

$$P_{S/H} = 1 - (P_{k/H_1} + P_{k/H_2} + P_{k/H_3}) + \qquad (2.10)$$
$$(P_{k/H_1} \times P_{k/H_2}) + (P_{k/H_1} \times P_{k/H_3}) + (P_{k/H_2} \times$$
$$P_{k/H_3}) - (P_{k/H_1} \times P_{k/H_2} \times P_{k/H_3})$$

Because of the assumption that only the component hit can be killed, and because none of the critical components overlap, the kills of the components are mutually exclusive. This means only one component can be killed by one hit, and the products of the P_{k/H_i} given in Equation 2.10 are not applicable. Therefore, Equation 2.10 simplifies to:

$$P_{S/H} = 1 - (P_{k/H_1} + P_{k/H_2} + P_{k/H_3}) \qquad (2.11)$$

and the probability of killing the aircraft given a hit on
the aircraft is just the sum of the individual probabilities
of killing each of the critical components given a random
hit on the aircraft. This may be written as:

$$P_{K/H} = P_{k/H_1} + P_{k/H_2} + \ldots + P_{k/H_N} \qquad (2.12)$$

Substituting Equation 2.6 into Equation 2.8, and applying
the concept of $P_{k/h}$ expressed in Equation 2.1, leads to:

$$P_{K/H} = A_V / A_P \qquad (2.13)$$

where A_V is the summation of vulnerable area of all of the
critical components.

For our example aircraft, the kill expres-
sion is given by:

$$Kill = (Pilot) .OR. (Fuel Tank) .OR. (Engine) \qquad (2.14)$$

From Equation 2.12:

$$P_{K/H} = P_{k/H_p} + P_{k/H_f} + P_{k/H_e} \qquad (2.15)$$

and

$$A_V = A_{V_p} + A_{V_f} + A_{V_e} \qquad (2.16)$$

where the subscripts p, f, and e denote the pilot, the fuel
tank, and the engine. From Equation 2.1, the individual
component areas are given by:

$$A_{V_p} = A_{P_p} \times P_{k/h_p} \qquad (2.17)$$

$$A_{V_f} = A_{P_f} \times P_{k/h_f} \qquad (2.18)$$

85

$$A_{v_e} = A_{p_e} \times P_{k/h_e} \qquad\qquad (2.19)$$

For illustration, a numerical example is presented in Table 3.

TABLE 3

**Nonredundant Model Without Overlap
With Mutually Exclusive Kill Modes**

Critical Component	A_{p_i}	x	P_{k/h_i}	=	A_{v_i}	P_{k/H_i}
Pilot	4 ft²		1.0		4 ft²	.0133
Fuel	60 ft²		0.3		18 ft²	.0600
Engine	50 ft²		0.6		30 ft²	.1000
$A_P = 300$ ft²			$A_V = 52$ ft²		$P_{K/H} = .1733$	

The kill of one critical component due to damage caused by a hit on another critical component and the consideration of multiple kill modes of a critical component can be indirectly accounted for, in this model, by increasing the numerical value of the kill criterion for the component hit. Consider two failure modes that are not mutually exclusive, that is, both can occur with a single hit. For example, suppose the probability the fuel tank of an aircraft is destroyed by a fire when the fuel tank is hit, is taken as 0.3. Suppose further that the probability that the fuel tank is penetrated and that hydraulic ram damage causes fuel to be dumped into the air inlet and ingested by the engine, leading to an aircraft loss, is taken as 0.1. The aircraft will survive a hit in the fuel

86

tank cnly if there is neither a fire nor any fuel ingesticn. The protability that neither of these failure modes cccur when the fuel tank is hit is civen by the product cf the protability that there is no fire (1 - 0.3), and the probability that there is no fuel ingestion kill of the engine (1 - 0.1), which is 0.63. Therefore, the probability that there will be a fire kill and/or a fuel ingestion kill, given a hit on the fuel tank, is given by (1 - 0.63), or C.37. A numerical example is presented in Table 4.

<div style="border:1px solid">

TABLE 4

Nonredundant Model Without Overlap With Mutually Inclusive Kill Modes

Critical Component	A_{p_i}	x	P_{k/h_i}	=	A_{v_i}	P_{k/H_i}
Pilot	4 ft²		1.0		4.0 ft²	.0133
Fuel	60 ft²		0.37		22.2 ft²	.0740
Engine	50 ft²		0.6		30.0 ft²	.1000

A_p = 300 ft² A_V = 56.2 ft² $P_{K/H}$ = .1873

</div>

Note that in this case the $P_{k/h}$ is nct the sum cf the two individual kill probabilities because there can be both a fire kill and a fuel ingestion kill on the one hit. Comparing Table 3 with Table 4 shows that by accounting for the additional failure mode of fuel irgestion by the engine increases the fuel tank $P_{k/h}$ with the acccmpanying change in compcnent and aircraft vulnerable area, and the compcnent and aircraft protability of kill. This same procedure can be used to compute the P_{k/h_i} due to multiple failure modes of one critical ccmponent.

87

(2) Aircraft Model Composed of Nonredundant
                Components with Overlap.   The aircraft
model will now be expanded by allowing two or more critical
components to overlap in an arbitrary manner.   An example
aircraft is presented in Figure 2.16.   There can be any
number of critical components along a shotline within the
overlap area.   For the aircraft to survive a hit along a
shotline within a region of N overlapping critical compo-
nents, each critical component along that shotline must
survive.   The probability the aircraft survives a hit on the
overlap region, P_{s/h_o}, is given by:

$$P_{s/h_o} = P_{s/h_1} \times P_{s/h_2} \times \cdots \times P_{s/h_N} \qquad (2.20)$$

Because two or more critical components in the overlap
region can be killed by one hit, the kills of more than one
component are not mutually exclusive.   In this case,
Equation 2.11 is not valid, and Equation 2.20 must be used
for hits in the overlap region.   For the aircraft illus-
trated in Figure 2.16, the probability the aircraft survives
a hit on the overlap region is given by Equation 2.21, where
the subscripts f and e refer to the fuel tank and the
engine.

$$P_{s/h_o} = P_{s/h_f} \times P_{s/h_e} \qquad (2.21)$$

            If the overlap area, A_{p_o}, is now consid-
ered as a separate component, the probability of kill given
a hit on the component may be written as:

$$P_{k/h_o} = 1 - P_{s/h_o} \qquad (2.22)$$

OVERLAP AREA, O

Figure 2.16   Nonredundant Aircraft Model With Overlap

and the vulnerable area of the overlap area, A_{v_o}, is given by:

$$A_{v_o} = A_{p_o} \times P_{k/h_o} \qquad (2.23)$$

Substituting Equation 2.21 into Equation 2.23, and using Equation 2.4, gives:

$$P_{k/h_o} = 1 - [\,(1 - P_{k/h_f}) \times (1 - P_{k/h_e})\,] \qquad (2.24)$$

It is assumed for this example that the overlap area in Figure 2.16 is 10 ft², the fuel tank $P_{k/h}$ is 0.3, the engine $P_{k/h}$ is 0.6, and all other areas are the same as used in the nonoverlapping example. The fuel is assumed to slow the damage mechanism down, but not enough to change the engine $P_{k/h}$. Because the $P_{k/h}$ values are the same as in the nonoverlapping example, any reduction in the vulnerable area of the aircraft is due only to the component overlap. Thus, in the overlap region:

$$P_{k/h_o} = 1 - [\,(1-0.3) \times (1-0.6)\,] = 0.72 \qquad (2.25)$$

and

$$A_{v_o} = 10 \times 0.72 = 7.2 \text{ ft}^2 \qquad (2.26)$$

according to Equations 2.23 and 2.24.

The vulnerable area of the overlap area contributes to the aircraft vulnerable area. However, overlapping also requires that the overlap area be subtracted from the total presented area of each overlapping component contributing to the overlap. The component area outside of the overlap is treated in the usual way. Table 5 illustrates computing the vulnerable area of an aircraft with

90

overlapping components. Note that locating two of the critical components such that one overlaps the other reduces the aircraft vulnerable area form 52 ft² to 50.2 ft². This is an example of how location of the critical components can reduce the aircraft's vulnerable area.

TABLE 5

Vulnerable Area Computation for Nonredundant
Model With Overlap and No Engine Fire

Critical Component	A_{p_i}	x	P_{k/h_i}	=	A_{v_i}
Pilot	4 ft²		1.0		4.0 ft²
Fuel	60-10=50 ft²		0.3		15.0 ft²
Engine	50-10=40 ft²		0.6		24.0 ft²
Overlap Area	10 ft²		0.72		7.2 ft²

$$A_v = 50.2 \text{ ft}^2$$

The net effect of component overlap can be a desirable reduction in aircraft vulnerable area provided the damage inflicted by the hit in the overlap area does not cause other problems. For example, consider a shotline through the fuel tank that overlaps the engine. Fuel could leak from the punctured tank onto hot engine parts, causing a fire. In this instance, the probability the engine is killed by the hit would probably be higher than 0.6. An example of the computation of aircraft vulnerable area, assuming the possibility of an engine fire, is given in Table 6. The overlapping area is assumed to be 10 ft², the fuel tank $P_{k/h}$ is assumed to be 0.3, and the $P_{k/h}$ for the

91

engine is taken as 0.9 because an engine fire is assumed to
occur nearly always due to a hit on the overlapping fuel
tank. Then,

$$P_{k/h_o} = 1 - [(1 - 0.3) \times (1 - 0.9)] \tag{2.27}$$

and the aircraft's vulnerable area increases to 52.3 ft².

TABLE 6

Vulnerable Area Computation for Nonredundant
Model With Overlap and an Engine Fire

Critical Component	A_{p_i}	x	P_{k/h_i}	=	A_{v_i}
Pilot	4 ft²		1.0		4.0 ft²
Fuel	60-10=50 ft²		0.3		15.0 ft²
Engine	50-10=40 ft²		0.6		24.0 ft²
Overlap Area	10 ft²		0.93		9.3 ft²

$$A_v = 52.3 \text{ ft}^2$$

Comparing the aircraft's vulnerable areas
given in Tables 3, 5, and 6 reveals that overlapping the
engine with the fuel tank reduces the vulnerable area from
52 ft² to 50.2 ft², provided no fire can occur. If a fire
is likely to occur, the vulnerable area increases form 52
ft² to 52.3 ft². Thus, overlapping nonredundant critical
components can reduce vulnerability provided that no undesi-
rable secondary kill modes occur.

Another facet of the overlap situation is
the change in the vulnerable area of the overlap area that

92

occurs when one of the components along a shotline has its vulnerability reduced by use of a vulnerability reduction technique. For example suppose the $P_{k/h}$ of the overlapping fuel tank is reduced from 0.3 to 0.0. The vulnerable area of the overlap section, with the possibility of a fire, is reduced from 7.2 ft² to 6.0 ft². This reduction appears to conflict with the fact that 10 ft² with a $P_{k/h}$ of 0.3, and a vulnerable area of 3.0 ft², has been made invulnerable. The reason for this apparent contradiction is the fact that the fuel tank is only one of two overlapping components. Generally, when the vulnerability of one component is reduced, the vulnerability of another component along the shotline will become more important. The vulnerable area of each component along the shotline is referred to as the true vulnerable area, and the components contribution to the overlap vulnerable area is referred to as the incremental vulnerable area. Using the data of Table 5, the true vulnerable areas are 3 ft² and 6 ft² for the overlapping fuel tank and engine areas, and the incremental vulnerable areas of the two overlapping components are 1.2 ft² and 4.2 ft² respectively.

(3) Aircraft Model Composed of Redundant Components with No Overlap. The nonredundant aircraft model described above will now be expanded by adding a second, separated engine, as shown in Figure 2.17. The second engine is assumed to have the same presented area as the first engine, 50 ft², but its $P_{k/h}$ is taken as 0.7 because of the presence of an additional accessory drive. For the purpose of comparison, the aircraft's presented area will remain 300 ft². The kill expression for this model aircraft is:

Kill = (Pilot) .OR. (Fuel Tank) .OR.   (2.28)
  [(Engine 1) .AND. (Engine 2)]

Figure 2.17   Redundant Aircraft Model With No Overlap

Table 7 presents the values for the vulnerability parameters. The Equation for the probability of aircraft survival given a random hit on the aircraft is:

$$P_{S/H} = P_{s/H_p} \times P_{s/H_f} \times [1 - (P_{k/h_{e1}} \times P_{k/h_{e2}})] \qquad (2.29)$$

which can be rewritten as:

$$P_{S/H} = (1 - P_{k/H_p}) \times (1 - P_{k/H_f}) \times \qquad (2.30)$$
$$[1 - (P_{k/H_{e1}} \times P_{k/H_{e2}})]$$

TABLE 7
Redundant Aircraft Model Without Overlap

Critical Component	A_{p_i}	x	P_{k/h_i}	=	A_{v_i}	P_{k/H_i}
Pilot	4 ft²		1.0		4 ft²	.0133
Fuel	60 ft²		0.3		18 ft²	.0600
Engine 1	50 ft²		0.6		30 ft²	.1000
Engine 2	50 ft²		0.7		35 ft²	.1167

$$A_p = 300 \text{ ft}^2 \qquad A_V = 22 \text{ ft}^2 \qquad P_{K/H} = .0733$$

Equation 2.30 says that the aircraft is killed if the pilot is killed, or if the fuel tank is killed, or if both engines are killed. Carrying out the multiplication indicated in Equation 2.30 leads to:

$$P_{S/H} = 1 - (P_{k/H_p} + P_{k/H_f}) + (P_{k/H_p} \times P_{k/H_f}) - \qquad (2.31)$$
$$(P_{k/H_{e1}} \times P_{k/H_{e2}}) + [P_{k/H_p} + P_{k/H_f} - (P_{k/H_p} \times$$
$$P_{k/H_f})] \times P_{k/H_{e1}} \times P_{k/H_{e2}}$$

95

MICROCOPY RESOLUTION TEST CHART

NATIONAL BUREAU OF STANDARDS 1963 A

If the assumption is made that the single hit cannot kill both engines (recall the assumption that only the component hit can be killed), then all of the component kills are mutually exclusive, and all of the products of the component kill probabilities in Equation 2.31 are zero. Hence, the aircraft is killed only if the pilot or the fuel tank is killed, and the $P_{K/H}$ and A_V are:

$$P_{K/H} = P_{k/H_p} + P_{k/H_f} \tag{2.32}$$

$$A_V = A_{v_p} + A_{v_f} \tag{2.33}$$

In general, only these components whose loss or damage can cause a kill of the aircraft on a single hit will contribute their vulnerable area to the total. If the single hit kills only one of the redundant components, the aircraft is not killed, and hence, nothing is contributed to the vulnerable area. Thus, the total vulnerable areas for this case is just the sum of vulnerable areas for each of the nonredundant critical components. Comparing Table 7 with Table 3 shows the single hit vulnerable area reduces from 52 ft² to 22 ft² due to the addition of the second engine. Thus, redundancy can significantly reduce the vulnerable area of the aircraft. On the other hand, if the damage to the redundant component which is hit creates secondary damage mechanisms or processes that propagate to another redundant component and kills that component, causing a loss of the aircraft, the redundant components will contribute to the aircraft vulnerable areas. For example, suppose the probability that a hit on one of the engines will cause that engine to throw blades into, or torch, or burn the other engine is 0.1. Because this can happen regardless of the engine hit, the component presented area becomes 50 + 50, or 100 ft², and the vulnerable area contributed by both engines

is 10 ft². Thus, this failure mode increases the aircraft vulnerable area to 32 ft².

(4) <u>Aircraft</u> <u>Model</u> <u>Composed</u> <u>of</u> <u>Redundant</u> <u>Components</u> <u>With</u> <u>Overlap</u>. If redundant components are now allowed to overlap one another, as shown by the aircraft in Figure 2.18, the computation of the vulnerable area given by Equation 2.29 must be modified because a single hit in the overlap region can kill both engines.

For this case, the cross hatched area shown in Figure 2.18 is defined as the overlap area. A single hit penetrating this area will have a probability of killing both redundant components, and hence the aircraft. Thus, it will be necessary to add the vulnerable area of the overlap region to that of the nonredundant critical components. In essence, the overlap region becomes another critical component, as in the nonredundant model with overlap. The vulnerable area is computed in the same manner as described previously; however, the details are slightly different. The expression for P_{s/h_o} given by Equation 2.20 must be modified. According to Equation 2.20, the probability that the aircraft survives a hit on an overlap area with no redundant components is given by:

$$P_{s/h_o} = P_{s_1} \times P_{s_2} \times P_{s_3} \times \ldots \times P_{s_N} \qquad (2.34)$$

However, if there are two redundant components among the components along the shotline, such as components number 2 and number 3, the probability that both are killed, which is assumed to cause an aircraft kill, is equal to the product of their individual probabilities of kill, $(P_{k/h_2} \times P_{k/h_3})$. The probability that both components are not killed, which is required for aircraft survival, is the complement of $(P_{k/h_2} \times P_{k/h_3})$, or $[1-(P_{k/h_2} \times P_{k/h_3})]$. Thus, $(P_{s_2} \times P_{s_3})$ in Equation 2.34 must be replaced with $[1-(P_{k/h_2} \times P_{k/h_3})]$ and the result is given by Equation 2.35.

97

Figure 2.18 Redundant Aircraft Model With Overlap

$$P_{s/h_o} = P_{s_1} \times [1 - (P_{k/h_2} \times P_{k/h_3})] \times \ldots \times P_{s_N} \qquad (2.35)$$

For our example, the probability the aircraft will survive a hit on the overlap region is given by:

$$P_{s/h_o} = 1 - (P_{s/h_{e1}} \times P_{s/h_{e2}}) \qquad (2.36)$$

and the probability of kill given a hit on the overlap region is:

$$P_{k/h_o} = 1 - [1 - (P_{k/h_{e1}} \times P_{k/h_{e2}})] \qquad (2.37)$$

This procedure can be extended to the situation where there are three or more redundant overlapping components or multiple sets of overlapping redundant components.

The "elsewhere" or non-overlapping areas of each of the redundant components are not used in the vulnerable area computations for the same reason as that used in the no overlap case. A single shotline through any one of the redundant components outside of the overlap region causes only a kill of that component, not of the aircraft, and hence no contribution is made to the aircraft vulnerable area. If the $P_{k/h}$ values for the engines in the overlap region shown in Figure 2.18 are taken as 0.6 for the first engine hit and 0.2 for the overlapped engine (the overlapping engine slows the damage mechanism down), the probability the aircraft will survive a hit on the overlap region is given by Equation 2.36 and is equal to 0.88. The probability of an aircraft kill given a hit in the overlap region is given by Equation 2.37 and is equal to 0.12. If the overlap area is assumed to be 10 ft², the vulnerable area increases to 23.2 ft² due to the overlapping engines as shown by the computation in Table 8.

TABLE 8

Redundant Aircraft Model With Overlap

Critical Component	A_{p_i}	x	P_{k/h_i}	=	A_{v_i}	P_{k/H_i}
Pilot	4 ft²		1.0		4.0 ft²	.0133
Fuel	60 ft²		0.3		18.0 ft²	.0600
Overlap Area	10 ft²		0.12		1.2 ft²	.0040

$$A_P = 300 \text{ ft}^2 \qquad A_V = 23.2 \text{ ft}^2 \qquad P_{K/H} = .0773$$

b. Multiple Hit Vulnerability

The analysis will now progress to the more reasonable expectation that in any combat engagement, an aircraft, if hit, will receive more than one hit. The distribution of these hits over the aircraft is assumed to be random, and all hits are assumed to travel along shot-lines from the same direction. This latter assumption is not required, but is taken for ease of explanation.

The probability the ith component still survives after n random hits on the aircraft, denoted by $\bar{P}_{k/H_i}^{(n)}$, is equal to the product of the component survival probabilities for each of the n hits on the aircraft. The superbar notation on P indicates the joint probability, and the superscript n in parentheses indicates the hit number. Thus,

$$\bar{P}_{s_i}(n) = P_{s/H_i}^{(1)} \times P_{s/H_i}^{(2)} \times \cdots \times P_{s/H_i}^{(n)} \qquad (2.38)$$

where P_{s/H_i} is the probability the ith component survives the jth hit on the aircraft. The probability of survival of

the ith component due to the jth hit on the aircraft is
equal to one minus the probability of kill of the ith compo-
nent due to the jth hit on the aircraft. Thus,

$$P_{s/H_i}^{(j)} = 1 - P_{k/H_i}^{(j)} \qquad (2.39)$$

Recall that P_{k/H_i} is assumed to be a constant value for all
j. Thus, Equation 2.38 can be given in the form:

$$P_{s/H} = \prod_{j=1}^{n} (1 - P_{k/H_i}^{(j)}) = [1 - P_{k/H_i}]^n \qquad (2.40)$$

The probability of survival of the aircraft
after n hits can be derived in a similar manner to give:

$$\bar{P}_{S/H}^{(n)} = \prod_{j=1}^{n} (1 - P_{K/H}^{(j)}) \qquad (2.41)$$

where $P_{K/H}^{(j)}$ is the probability of kill of the aircraft due to
the jth hit on the aircraft, and may or may not be constant
for all j. The probability the aircraft is killed after n
hits, $\bar{P}_{K/H}^{(n)}$, is the complement of $\bar{P}_{S/H}^{(n)}$, or:

$$P_{K/H}^{(n)} = 1 - P_{S/H}^{(n)} = 1 - \prod_{j=1}^{n} (1 - P_{K/H}^{(j)}) \qquad (2.42)$$

In any multiple hit assessment, it is necessary
to keep in mind the distinction between the effect of
multiple hits on the vulnerable area of a nonredundant
aircraft model as opposed to hits on a redundant aircraft
model. Multiple hits on a nonredundant aircraft model do
not change the total vulnerable area and the $P_{K/H}$ because of
the assumption that components are either fully functional
or killed. If a shot hits the aircraft, but not a critical
component, the vulnerable area and the $P_{K/H}$ remain the same.
Only when a hit actually strikes the vulnerable area of a
nonredundant critical component is the aircraft killed.

The redundant aircraft model has to be viewed differently. If the redundant aircraft takes the first hit in the vulnerable area of a redundant component, the aircraft is not killed, but the aircraft vulnerable area and the $P_{K/H}$ will increase for the second hit because one of the redundant components has been killed. For instance, if one of two engines is killed on the first hit, the aircraft vulnerable area is now increased by the vulnerable area of the remaining engine because a kill of the remaining engine on a subsequent hit causes an aircraft kill.

Three methods are presented below to show the effects of multiple hits: The kill tree diagram, the state transition matrix (or Markov chain) method, and a simplified approach. The first method is more of an instructional tool, whereas the transition matrix method can be used in complex problems beyond the practical capability of the kill tree diagram. The simplified approach is the easiest to use.

(1) The Kill Tree Diagram. The sequence of events explained above regarding the effects of multiple hits can be illustrated diagrammatically using what is known as a kill tree diagram. The probability of kill of each component given a random hit on the aircraft is first computed using Equation 2.6, then the kill tree diagram is created. To simplify the explanation, consider the nonredundant aircraft model with no overlap illustrated in Figure 2.15 and defined in Table 3.

The Kill Tree Diagram, Nonredundant Model. Figure 2.19 presents the kill tree diagram that defines the mutually exclusive kill probabilities of each nonredundant critical component (pilot, fuel, and engine), and hence the aircraft, and the probability that no critical components are killed after the first hit on the aircraft.

102

Figure 2.19   First Hit Nonredundant Kill Tree

In Figure 2.19,   P $= P_{k/H_p}$,   F $= P_{k/H_f}$,   E $= P_{k/H_e}$,   and N represents the probability that no critical components are killed and is given by N $= 1-(P+F+E)$.   Note that P+F+E+N is unity; all possibilities have been accounted for on this first hit.   The probability the aircraft is killed on this first hit is given by P+F+E.

Figure 2.20 represents the kill tree diagram after the second hit.   PxP represents the situation where the first hit killed the pilot, and the second hit also killed the pilot.   It is important to note, however, that once a probability of kill is defined for each critical component on the first hit,   that component is considered killed at that probability value for all subsequent hits. The pilot cannot be killed twice.   The four branches from that kill probability for the second hit adds nothing new (no additional probability of pilot kill) to the sequence. This fact can be verified by examining the sum of the kill probabilities PxP PxF PxE PxN, which is the same as Px(P+F+E+N).   Thus, this line is equal to the probability calculated for P on the first hit because P+F+E+N is unity. The only addition to the kill probability of the aircraft due to the second hit comes from critical components not killed on the first hit.   This concept will become clearer and more important when redundant components are discussed.

Figure 2.20   Second Hit Nonredundant Kill Tree

In order to illustrate the development of a kill tree diagram, assume the numerical values for the component kill probabilities given in Table 3.   Figure 2.21 illustrates the kill tree for the first hit.   The

Figure 2.21   First Hit Nonredundant Kill Tree Example

probability the aircraft is killed after the first hit is the sum of the kill probabilities for each of the critical components.   Thus,

$$\tilde{P}^{(1)}_{K/H} = .0133 + .0600 + .1000 = 0.1733 \tag{2.43}$$

104

and hence,

$$\bar{P}_{S/H}^{(1)} = 1 - 0.1733 = 0.8267 \tag{2.44}$$

Figure 2.22 extends this example to the second hit. The probability the aircraft is killed after the second hit is the sum of the additional kill probabilities for each of the critical components for the second hit. Thus,

$$\bar{P}_{K/H}^{(2)} = \bar{P}_{K/H}^{(1)} + [0.8267 \times (.0133 + .0600 + .1000)] \tag{2.45}$$

and hence,

$$\bar{P}_{S/H}^{(2)} = 1 - \bar{P}_{K/H}^{(2)} = 1 - .3166 = .6834 \tag{2.46}$$

Figure 2.22 Second Hit Nonredundant Kill Tree Example

The kill tree diagram procedure may be continued indefinitely to determine $\bar{P}_{S/H}$ for any number of

hits. However, the probability the nonredundant aircraft model survives a sequence of hits can also be computed using Equation 2.41. For the nonredundant aircraft model, $P_{K/H}$ is constant as explained above. Thus, the probability the aircraft survives two hits is given by:

$$\bar{P}_{S/H}^{(2)} = (1 - P_{K/H}^{(1)}) \times (1 - P_{K/H}^{(2)}) = (1 - P_{K/H})^2 \qquad (2.47)$$

or,

$$\bar{P}_{S/H}^{(2)} = (1 - 0.1733)^2 = 0.6834 \qquad (2.48)$$

Note that this value is the same as that obtained from the kill tree diagram, as it should be.

Equation 2.41 can be used for any number of hits and is much easier to use than the kill tree diagram. The essence of this equation is that all of the nonredundant critical components can be combined into one composite critical component whose vulnerable area is 52 ft^2 and whose $P_{K/H}$ is 0.1733 in the numerical example.

Kill Tree Diagram, Redundant Model. Consider now the redundant aircraft model shown in Figure 2.17 and defined in Table 7. An evaluation for $\bar{E}_{K/H}^{(n)}$ and $\bar{P}_{S/H}^{(n)}$ can be performed in a manner similar to the previous discussion. Although the engines are redundant critical components, each must be shown as a separate branch in the kill tree diagram, because a kill of an engine is a possible outcome of an aircraft hit; and any engine kill will have an effect on the aircraft's vulnerability. Figure 2.23 illustrates the kill tree diagram for the first hit. Note that N now represents the probability that no nonredundant or redundant component is killed.

The logical kill expression for this redundant aircraft model is given by Equation 2.49.

Figure 2.23   First Hit Redundant Kill Tree Example

(Pilot) .OR. (Fuel Tank) .OR.   (2.49)
[(Engine 1) .AND. (Engine 2)]

Because the first hit cannot kill both engines, the prob-
ability that the aircraft is killed after the first hit is
just the sum of the kill probabilities for each of the
nonredundant critical components (pilot and fuel). Thus,

$$\bar{P}_{K/H}^{(1)} = 0.0133 + 0.0600 = 0.0733 \qquad (2.50)$$

Figure 2.24 illustrates the event prob-
abilities on the second hit after a kill of engine 1 on the
first hit.   The sequence represented by killing engine 1 on
the first hit and then killing the pilot (0.00133), or fuel
(0.0600), or engine 2 (0.01167) on the second hit results in
additional aircraft kills. Thus, the cumulative probability
of an aircraft kill is due to kills of the nonredundant
critical components as well as kills defined by component
redundancy restrictions.   The five branches from a kill of
engine 2 and from the N branch will also contribute addi-
onal kills.   Thus, after two hits, the cumulative prob-
ility of kill is given by Equation 2.51.

107

Figure 2.28   Sample Component Vulnerable Area For▪

projectile, or in a sketch of the aircraft with regicns
shown and the region's presented area and vulneratle area
summarized on an acccmpanying fcrm.

2. **Blast**

Aircraft vulnerability to external blast is usually
expressed as an envelcpe about the aircraft where the deto-
nation of a specified charge weight of spherical uncased

Assessment date _____

Performing organization _____

Kill category _____

Aircraft _____

Threat _____

Total A_V, ft² (m²)

Projectile V_S, ft/sec (m/sec)	Left side	Right side	Top	Bottom	Front	Rear
500 (152.4)						
1,000 (304.8)						
1,500 (457.2)						
2,000 (609.6)						
2,500 (762.0)						
3,000 (914.4)						
3,500 (1066.8)						

Figure 2.27   Total Aircraft Single Hit Vulnerable Form

components for each combination of threat, kill category, and striking aspect assessed with the striking velocity varying from 500 to 3500 ft/sec. Manual assessments for nonexplosive projectiles will be performed for at least the six major views of the aircraft. A computerized assessment will be performed for at least the six major views and usually for a total of 26 views spread at 45 degree increments of elevation and azimuth as described earlier. A typical total aircraft single hit vulnerable area summary form is shown in Figure 2.27. Multiple hit vulnerable area curves similar to the one shown in Figure 2.26 should also be presented for at least six aspects.

In addition to the total aircraft A_v presentation, the vulnerable area of each critical component should also be listed, and both the true and the incremental vulnerable areas should be presented for overlapping components. Redundant components should be identified, and the number of redundant components that must be killed to cause an aircraft kill should be noted. The single hit vulnerable area associated with overlapping redundant components should also be identified. Figure 2.28 shows a sample component vulnerable area summary form.

For explosive projectiles and contact fuzed missiles, vulnerability data normally will be presented as summary forms of the total A_v of nonredundant components for each combination of threat, kill category, and aspect angle assessed. These results usually are not presented as varying with the fragment striking velocity. Each major redundant component will be shown separately if assessed. Assessments will be performed for at least the six major views and for 26 views if possible. For HE projectiles, in addition to the total aircraft vulnerable area, the contribution by subsystem or aircraft region should also be presented. This can be done similar to the nonexplosive

Figure 2.26   Vulnerable Area vs Number of Hits

118

$$1 - P_{K/H}^{(n)} = (\bar{P}_{S/H}^{(n)}) / (\bar{P}_{S/H}^{(n-1)}) \qquad (2.61)$$

Equation 2.61 can also be given in the form:

$$1 - P_{K/H}^{(n)} = (1 - \bar{P}_{K/H}^{(n)}) / (1 - \bar{P}_{K/H}^{(n-1)}) \qquad (2.62)$$

and hence,

$$P_{K/H}^{(n)} = (\bar{P}_{K/H}^{(n)} - \bar{P}_{K/H}^{(n-1)}) / (1 - \bar{P}_{K/H}^{(n-1)}) \qquad (2.63)$$

The vulnerable area for the nth hit, $A_V^{(n)}$, is computed using the $\bar{P}_{K/H}^{(n)}$ given by Equation 2.63 and the basic vulnerable area equation, Equation 2.1. Thus,

$$A_V^{(n)} = (A_p) (\bar{P}_{K/H}^{(n)}) \qquad (2.64)$$

Figure 2.26 shows the $A_V^{(n)}$ for the redundant model $\bar{P}_{K/H}^{(n)}$ given in Figure 2.25. Note that the $A_V^{(1)}$ is just the sum of the vulnerable areas of the nonredundant components. Note also the asymptotic behavior for the redundant model. The constant vulnerable area of the nonredundant aircraft given in Table 3 is also plotted in Figure 2.26 for the purpose of comparison. Note that the vulnerable area of the redundant aircraft is less than that of the nonredundant aircraft (with the 30 ft² vulnerable area engine) for the first fifteen hits. On subsequent hits, the vulnerable area is slightly larger due to the fact that there is a strong likelihood that one or the other of the two engines has been killed, and the benefits of redundancy have been eliminated.

c. Presentation of Results

Nonexplosive projectile results normally will be presented in summary forms of total A_V of nonredundant

117

aircraft designs due to its dependence on the physical size
of the aircraft. If two aircraft have identical vulnerable
areas, but different presented areas, the one with the
largest presented area will appear to be less vulnerable
because its cumulative probability of kill given n hits will
be less than that of the aircraft with the smaller presented
area. On the other hand, being larger, it may suffer more
hits; that is, it may be more susceptible.

The measure that is the most meaningful
for vulnerability assessment and comparison of designs is
vulnerable area. For nonredundant aircraft, the probability
of kill given a hit and the vulnerable area are constant for
each and every hit. Each subsequent hit has just as much
chance of killing the aircraft as the previous hit (assuming
component degradation is neglected). However, this is not
true for aircraft with redundant critical components. For
these aircraft, the probability of kill given a hit and the
corresponding vulnerable area changes with each hit because
of the increasing possibility of the loss of one or more of
the redundant components. In order to compute the multiple
hit vulnerable area, an event-based probability of kill
given a hit must be computed for each hit. In general, the
probability of aircraft survival after taking n hits was
given by Equation 2.41 which is:

$$\bar{P}_{S/H}^{(n)} = (1-P_{K/H}^{(1)})(1-P_{K/H}^{(2)}) \cdot \cdot \cdot (1-P_{K/H}^{(n)}) \tag{2.59}$$

which also can be expressed in the form:

$$\bar{P}_{S/H}^{(n)} = (\bar{P}_{S/H}^{(n-1)})(1-\bar{P}_{K/H}^{(n)}) \tag{2.60}$$

The value desired in Equation 2.60 is $\bar{P}_{K/H}^{(n)}$, the event-based
probability that the aircraft is killed on the nth hit on
the aircraft given that it has survived the first (n-1)
hits. Rearranging terms in Equation 2.60 gives:

116

$$\overline{P}_{S/H}^{(n)} = (1-\overline{P}_{k/H_p}^{(n)})(1-\overline{P}_{k/H_f}^{(n)})(1-(\overline{P}_{k/H_{e1}}^{(n)})(\overline{P}_{k/H_{e2}}^{(n)})) \qquad (2.56)$$

where

$$\overline{P}_{k/H_p} = 1 - (1-P_{k/H_p})^n \ , \ \overline{P}_{k/H_f} = 1 - (1-P_{k/H_f})^n \qquad (2.57)$$

and

$$(\overline{P}_{k/H_{e1}}^{(n)})(\overline{P}_{k/H_{e2}}^{(n)}) = (1-(1-P_{k/H_{e1}})^n)(1-(1-P_{k/H_{e2}})^n) \qquad (2.58)$$

according to Equation 2.40. Table 10 presents the $\overline{P}_{K/H}^{(n)}$ for both the transition matrix method and the simplified approach for several values of n. Note that the approximate $\overline{P}_{K/H}^{(n)}$ is both lower than and higher than the correct answer and that the approximate kill probability is reasonably close to the correct value, for this example.

TABLE 10

A Comparison of Aircraft Kill Probabilities

Hits, n	1	3	5	10	20
$\overline{P}_{K/H}^{(n)}$ Correct	.0733	.2615	.4456	.7619	.9640
$\overline{P}_{K/H}^{(n)}$ Approximate	.0833	.2693	.4436	.7470	.9567

---

(4) **Multiple Hit Vulnerable Area.** The cumulative probability of kill given n hits derived above is not necessarily the best measure for assessing or comparing

Figure 2.25 Probability of Kill for the Redundant
Aircraft Model vs the Number of Hits

percent probability that engine 1 has been killed, a 17.93 percent probability that engine 2 has been killed, and a 50.41 percent probability that none of the critical components have been killed. Thus, after the second hit:

$$\bar{P}^{(2)}_{K/H} = 0.1413 + 0.0233 = 0.1646 \tag{2.55}$$

This value is the same as that obtained from the kill tree diagram after the second hit, as it should be. This process can easily be continued for as many hits as desired. Figure 2.25 shows the $\bar{P}^{(n)}_{K/H}$ as a function of n for both the redundant aircraft model and the nonredundant aircraft model given in Table 3. The difference between the two curves is the reduction in vulnerability due to redundancy.

In the above presentation, the transition matrix was assumed to be the same for all hits. This assumption is not necessary. If multiple damage mechanisms hit the aircraft from several different aspects, a transition matrix can be constructed for each aspect of interest. The computation of the state vector for the $j+1$ hit, given by Equation 2.53, would use the transition matrix for the approach direction of that particular hit. Another possible modification is the consideration of an increase in P_{K/H_i} due to multiple hits. Again, [T] could be changed from one hit to the next.

(3) A Simplified Approach. If the probability of survival of each of the critical components after n hits on the aircraft is known, an approximation for the probability the aircraft has been killed by the n hits can be obtained by neglecting the mutually exclusive feature of the individual component kills on any one hit. Thus, for the example redundant component aircraft model, Equation 2.30 can be used. Equation 2.30, for the n hit situation, is given by Equation 2.56.

113

where $Knrc^{(n)}$ and $Krc^{(n)}$ are the probabilities the aircraft is in these two states after n hits.

Using the numbers generated in the previous numerical example, consider the first hit. Prior to the first hit, the aircraft is entirely in the NK state. Thus, according to Equation 2.53:

$$[S]^{(1)} = [T][S]^{(0)} = [T] \begin{bmatrix} 0 \\ 0 \\ 0 \\ 0 \\ 1 \end{bmatrix} NK$$

Carrying out the matrix multiplication gives:

$$[S]^{(1)} = \begin{bmatrix} 0.0773 \\ 0.1000 \\ 0.1167 \\ 0 \\ 0.7100 \end{bmatrix} \begin{matrix} Knrc \\ \\ \\ Krc \\ \end{matrix}$$

Thus, $\bar{P}_{K/H}^{(1)} = 0.0733$ as before. Similarly, for the second hit:

$$[S]^{(2)} = [T][S]^{(1)} = [T] \begin{bmatrix} 0.0733 \\ 0.1000 \\ 0.1167 \\ 0 \\ 0.7100 \end{bmatrix}$$

Carrying out the matrix multiplication gives:

$$[S]^{(2)} = \begin{bmatrix} 0.1413 \\ 0.1520 \\ 0.1793 \\ 0.0233 \\ 0.5401 \end{bmatrix} \begin{matrix} Knrc \\ \\ \\ \\ Krc \end{matrix}$$

Note that the sum of the elements of [S] is unity, as it should be. The $[S]^{(2)}$ vector results reveal that after the second hit there is a 14.13 percent probability that either the pilot or the fuel tank or both have been killed, a 15.20

Krc1) is the sum of engine 1's probability of kill given a hit on the aircraft, E1, and that of the remaining "elsewhere" area of the aircraft, N. Transitioning from Krc1 to Krc2 is zero because a kill of the second engine after the first engine is killed defines the state Krc. Thus, the state transitions from Krc1 to Krc according to the conditional probability of kill of the second engine, E2, and so on.

Let the probability that the aircraft exists in each of the five possible states after the jth hit be expressed by a vector $[S]^{(j)}$, where

$$[S]^{(j)} = \begin{bmatrix} Knrc \\ Krc1 \\ Krc2 \\ Krc \\ NK \end{bmatrix}$$

Note that the sum of the elements in $[S]^{(j)}$ is always unity; the aircraft must exist in one of these five states. The probability the aircraft is in each one of the five states after the (j+1)th hit is given by:

$$[S]^{(j+1)} = [T][S]^{(j)} \qquad (2.53)$$

That is, the aircraft transitions from $[S]^{(j)}$ to $[S]^{(j+1)}$ according to $[T]$.

An aircraft kill is defined by those states that specify either a kill of any of the nonredundant components or a kill of enough members of the sets of redundant components, such as both engines. In this example, Knrc and Krc specify the kill states. Hence, the probability the aircraft is killed after n hits is given by:

$$\bar{P}_{K/H}^{(n)} = Knrc^{(n)} + Krc^{(n)} \qquad (2.54)$$

111

A transition matrix of probabilities, [T], can now be constructed to specify how the aircraft will transiticn from one state to another due to a hit cn the aircraft. Table 9 illustrates the computation of the [T] matrix for the example redundant aircraft model defined in Table 7. Each element of the matrix represents the

---

TABLE 9

Computation of the State Transition Matrix

Probability cf transitioning from this state

	Knrc	Krc1	Krc2	Krc	NK	to this state
	300	4+18	4+18	0	4+18	Knrc
	0	30+213	0	0	30	Krc1
$\frac{1}{300}$	0	0	35+213	0	35	Krc2
	0	35	30	300	0	Krc
	0	0	0	0	213	NK

Note that the sum of each column is unity

---

probability of transitioning from the state defined by the column lccations to the new state defined by the rcw location. The matrix is read as follows. The probability of the aircraft transiticning frcm the Knrc state to the Knrc state is unity (300/300) because Knrc is an absorbing state. The protability of transitionirg from the Krc1 state (kill of engine 1) to the Knrc state (kill of a nonredundant component) is the sum of the conditional probabilities of kill cf the two nonredundant components, that is, P+F. The probatility of transitioning frcm Krc1 to Krc1 (remaining in

110

(2) The State Transition Matrix Method (Markov
Chain).   Briefly, the state transition
matrix method assumes that a sequence of independent events
(random hits on the aircraft) can be modelled as a Markov
process.   In a Markov process,   the aircraft is defined to
have two or more states in which it may reside,   and the
probability of an aircraft kill due to the j+1 hit is the
probability that the j+1 hit on the aircraft will cause the
aircraft to transition from a non-kill state after j hits to
a kill state.   The sequential process of evaluating the
probability the aircraft exists in each of the several
possible states after hits 1, 2, 3, ..., J is based upon the
probability the aircraft existed in each of the possible
states after hits 0, 1, 2, ..., J-1, respectively, and is
referred to as a Markov chain.   Rather than dwell on the
mathematical theory, an example using the previously defined
redundant aircraft model will serve much better to illus-
trate the methodology.

An aircraft consisting of a pilot, a fuel
tank, and two engines can exist in five distinct states:

1. One or more of the nonredundant critical components
   (the pilot and the fuel tank) have been killed,
   resulting in an aircraft kill, denoted by Knrc.

2. Only engine 1 has been killed, denoted by Krc1.

3. Only engine 2 has been killed, denoted by Krc2.

4. Both engine 1 and engine 2 have been killed,
   resulting in an aircraft kill, denoted by Krc.

5. None of the nonredundant critical components and
   neither of the engines are killed, denoted by NK.

States Knrc and Krc are called absorbing states because the
aircraft cannot transition from these two kill states to any
of the other three non-kill states.

109

Figure 2.24   Second Hit After First Hit on Engine 1

$$\bar{P}_{K/H}^{(2)} = .0733 + [.1000 \text{ x } (.0133 + .0600 + .1167)] \quad (2.51)$$
$$+ [.1167 \text{ x } (.0133 + .0600 + .1000)]$$
$$+ [.7100 \text{ x } (.0133 + .0600)] = 0.1646$$

and hence:

$$\bar{P}_{S/H}^{(2)} = 1 - 0.1646 = 0.8354 \qquad (2.52)$$

Note the significant increase in survivability (0.8354 versus 0.6834) after the second hit due to the addition of the second engine.

This procedure can be continued indefinitely, as in the nonredundant case, but it is obvious that the computations quickly become overwhelming in complexity. The state transition matrix method described below is better suited to handle the problem.

pentolite high explosive will result in a specified level of damage or kill to the aircraft. Detonation outside of such an envelope will result in little or no damage to the aircraft or in a lesser kill level. The damage mechanism is the blast resulting from the detonation of the high explosive in the vicinity of the aircraft. A spectrum of charge weights are often specified for which the aircraft vulnerability measures are computed in the vulnerability assessment. The specific charge weights selected are representative of the expected threat warheads which might be encountered. Envelopes are determined for a variety of encounter conditions which account for variations in aircraft speed and altitude, as well as aspect. Aircraft critical components vulnerable to the external blast consist principally of portions of the airframe structure and control surfaces. Threshold kill criteria for the critical components are derived from structural and aerodynamic analyses. Once the blast pressures and impulse levels required for a component kill are determined for several locations on the aircraft surface, a contour may be plotted corresponding to the detonation distance and the weight of pentolite which will provide the required overpressure and impulse level. Two different graphical presentations of the data may be used. The first is a plot of charge weight versus distance for a constant kill level. Several curves can be drawn on the same graph, one for each altitude of interest. A similar graph is required at each azimuth and elevation angle of interest about the aircraft. Figure 2.29 is an example of this type of presentation. The second graphical method, illustrated in Figure 2.30, is to construct iso-charge weight contours about the aircraft for a given kill level and altitude in all planes of interest.

Figure 2.29   Typical External Blast
Vulnerability Data Presentation

3. Endgame Analysis

The probability of an aircraft kill due to the burst
of a specific warhead for a particular set of encounter
conditions, $P_{K/D}$, is dependent upon how many fragments hit
the aircraft and the aircraft's vulnerability to the
multiple hits.   The number of fragments which strike the
aircraft was derived in the previous chapter and the
aircraft's vulnerability to multiple hits was discussed in
the previous section.   The $P_{K/D}$ due to the n hits on the
aircraft is analogous to the $\bar{P}_{K/H}^{(n)}$ derived in this chapter
earlier.   Thus, $P_{K/D}$ can be estimated using cumulative

123

Figure 2.30   Typical External Blast K-Kill Contour for Various Weights of Uncased Pentolite at Sea Level

probability of kill curves similar to the one shown in Figure 2.25. Simplified equations for $P_{K/D}$ in terms of the aircraft vulnerable area and the n hits are derived below.

The probability the aircraft is killed given the jth random hit by a single fragment, $\overline{P}_{K/H}^{(n)}$, can be determined using the procedure described in this chapter. The probability that the aircraft is killed by the n independent, random hits from detonation, $\overline{P}_{K/H}^{(n)}$, is given by Equation 2.42. Therefore,

$$\overline{P}_{K/H}^{(n)} = P_{K/D} = 1 - \prod_{j=1}^{n} (1 - P_{K/H}^{(j)}) \qquad (2.65)$$

124

It can be shown that for small $P_{K/H}^{(j)}$,

$$\prod_{j=1}^{n} (1 - P_{K/H}^{(j)}) = \exp(- \sum_{j=1}^{n} P_{K/H}^{(j)}) \qquad (2.66)$$

Furthermore,

$$\sum_{j=1}^{n} P_{K/H}^{(j)} = \sum_{j=1}^{n} A_{V}^{(j)} / A_{P} \qquad (2.67)$$

Hence, $P_{K/D}$ can be given in the form:

$$P_{K/D} = 1 - \exp((- \rho / n) \sum_{j=1}^{n} A_{V}^{(j)}) \qquad (2.68)$$

according to Equation 1.33. If there are no redundant crit-ical components, $A_{V}^{(j)}$ is usually assumed to be a constant value for all hits, and $P_{K/D}$ simplifies to:

$$P_{K/D} = 1 - \exp(- \rho A_{V}) \qquad (2.69)$$

An example of the computation of $P_{K/D}$ for an encounter is given in Table 11.

There is no unique value for $P_{K/D}$ for a warhead detonation at a specific location with respect to the aircraft. $P_{K/D}$ will be different for detonations at the same distance, but at different locations around the aircraft. Nevertheless, the aircraft's vulnerability to an externally detonating warhead is often indicated only with respect to the distance of the detonation from the aircraft, without regard to the other variables.

A typical curve relating $P_{K/D}$ to the detonation distance, R, is given in Figure 2.31. This curve is referred to as the kill function given a detonation, and the radius at which $P_{K/D}$ is equal to 0.5 is called the lethal radius of the warhead. The value of $P_{K/D}$ specified for each value of R could be the average of the $P_{K/D}$'s computed for

Figure 2.31 Typical Probability of Kill
Given A Detonation Function

```
+-------------------------------------------------------------------+
|                                                                   |
|                          TABLE 11                                 |
|                                                                   |
|              An Example Computation for $P_{K/D}$                  |
|                                                                   |
|   Static Warhead      Spray angles, $\alpha_1$ = 50, $\alpha_2$ = 120 |
|   Parameters                                                      |
|                       Number of fragments, N = 1000               |
|                                                                   |
|                       Fragment velocity, $V_i$ = 7000 fps         |
|                                                                   |
|                                                                   |
|   Encounter           Missile speed, $V_m$ = 1500 fps            |
|   Parameters                                                      |
|                       Missile angle, $\theta$ = 30                |
|                                                                   |
|                       Detonation distance, R = 80 ft              |
|                                                                   |
|                       Aircraft speed, $V_t$ = 1000 fps           |
|                                                                   |
|                                                                   |
|   Aircraft            Aircraft presented length = 50 ft           |
|   Parameters                                                      |
|                       Aspect vulnerable area, $A_V$ = 25 ft$^2$   |
|                                                                   |
|                       (to fragment size and striking             |
|                        velocity under consideration)             |
|                                                                   |
|                                                                   |
|   Fragmentation       $\phi_1$ = Tan$^{-1}$[7644 / 1515] - 30     |
|   Dynamic Spray                                                   |
|   Angles              $\phi_2$ = Tan$^{-1}$[4250 / -5763] - 30    |
|                                                                   |
|                                                                   |
|   Fragment            $\rho$ = 1000 / [2 x  x 80$^2$ x 1.059]     |
|   Spray Density                                                   |
|                       $\rho$ = .0235 fragments/ft$^2$             |
|                                                                   |
|                                                                   |
|   Probability         $P_{K/D}$ = 1 - exp(-0.0235 x 25)           |
|   of kill                                                         |
|                       $P_{K/D}$ = 0.44                            |
|                                                                   |
+-------------------------------------------------------------------+
```

several different encounters at R, or the $P_{K/D}$ values could be weighted with respect to the expected probability of encounter occurrence in order to obtain a weighted average. For example, if a certain missile only approaches the aircraft from the rear aspect, only $P_{K/D}$ values for that type of encounter would be computed.

E. VULNERABILITY TO INTERNALLY DETONATING HE WARHEADS

Anti-aircraft projectiles 20mm and larger often have an
HE core with a contact fuze that detonates the warhead
either immediately or shortly after impacting the aircraft.
This results in a detonation on or inside the aircraft, with
the accompanying blast and fragment spray in many direc-
tions. The assumption of parallel trajectories or shotlines
through the aircraft used in the nonexplosive penetrator
vulnerability assessment is not valid in this situation.
Instead, the fragment shotlines emanate radially from the
location of the warhead burst point. The probability of
kill of any critical components that lie on any of the
radial fragment shotlines needs to be evaluated and the
aircraft's vulnerable area and probability of aircraft kill
given a hit computed.

There are several approaches to this problem. One
simple approach is to expand the presented area of each of
the critical components beyond the actual physical size of
the component, and then treat a hit by the HE round in the
expanded area in the same manner as that used for the
nonexplosive penetrator. For example, the presented area of
the pilot could be the entire cockpit, because any hit and
detonation within the cockpit could kill the pilot. Figure
2.32 illustrates this approach. If the expanded areas of
two or more components intersect or overlap, the procedure
for accounting for overlapping components described above
must be used.

In another procedure, the warhead detonation is assumed
to take place at individual locations within a grid superim-
posed on the presented area of the aircraft, as illustrated
in Figure 2.33. Each cell contains one randomly located
burst point. The probability of killing the aircraft is
then evaluated for each burst point. This kill probability

128

EXPANDED AREA A_{pe_i}

$$P_{K/H} = \frac{A_V}{A_P} \qquad A_V = \sum_{i=1}^{3} A_{pe_i} * P_{k/h_i}$$

Figure 2.32   The Expanded Area Approach

Figure 2.33   The Point Burst Approach

will be dependent upon the relative location of the adjacent
critical components and on any shielding of these components
provided by intervening structure and non-critical compo-
nents. Critical components, or parts of critical compo-
nents, outside of the cell in which the burst occurs must
also be considered when they can be hit and killed by the
damage mechanisms. Note that several redundant critical
components can possibly be killed by the single HE burst.
The burst point kill probability is determined using the
kill expression for the aircraft. However, because more
than one critical component can be killed given a single
burst, the individual component kills are not exclusive; a
single burst could kill both the fuel system and the pilot.
Thus, the approach used in the overlapping component model
to compute P_{k/h_o} must also be used here. The probability of
an aircraft kill given a random hit from the attack aspect
under consideration is obtained by multiplying the prob-
ability of aircraft kill given a hit computed for each burst
point, P_{K/H_b}, by the probability of a random shot hitting
the burst point area, P_{H_b}. The latter probability is given
by:

$$P_{H_b} = A_b / A_p , \qquad b = 1, 2, \ldots, B \qquad (2.70)$$

where B is the number of burst points or cells considered,
and A_b is the local grid cell area around each burst point.
Note that even though critical components outside of the
cell are included in P_{K/H_b}, just the area of the cell itself
is used in the computation. The $P_{K/H}$ for the aircraft given
a random hit is given by:

$$P_{K/H} = \sum_{b=1}^{B} (P_{H_b})(P_{K/H_b}) = A_p \sum_{b=1}^{B} (A_b)(P_{K/H_b}) \qquad (2.71)$$

where A_{v_b} is the vulnerable area of the bth cell.

131

The aircraft vulnerable area is computed using:

$$A_V = \sum_{b=1}^{B} A_b \, (P_{K/H_b}) = \sum_{b=1}^{B} A_{V_b} \qquad (2.72)$$

which is the sum of the vulnerable area of the individual cells.

The vulnerable area for internally detonating HE warheads is usually much larger than the vulnerable area for nonexplosive projectiles and fragments, but it can never exceed the aircraft's presented area.

F. VULNERABILITY TO LASERS

Because a laser beam must hit an aircraft to damage it, and because no high explosive charge is involved, the methodology for assessing the vulnerability of aircraft to lasers consists of essentially the same procedure as used in the assessment of aircraft vulnerability to the single nonexplosive penetrator.

Laser vulnerability is particularly threat sensitive. The first step of the assessment consists of developing a description of the target. Foreign intelligence data and mirror technology are used to describe the target. From this data a computerized target description is generated, allowing the critical components and their failure modes to be identified. The second step of a laser vulnerability study is to accumulate data on the energy density required to produce failure of the critical components, and energy density data on the barrier materials which shield the critical components. From this data, burn through times are calculated as a function of laser beam intensity, power, type of material, and thickness using a parametric penetration equation. A shotline program, using the computerized target description, is used to determine the critical

components and thickness of the shielding material which must be penetrated along each shotline. For each laser dwell time interval, energy is allowed to accumulate, and the time it takes for critical component failure is recorded. An aiming accuracy function is applied for each shotline and the probability of kill, given a laser locked onto target, $P_{K/Lo}(t)$, for each dwell time is calculated.

The general description of laser vulnerability assessment described above applies only to aircraft and ends with $P_{K/Lo}(t)$. Laser vulnerability assessment of a missile is more complicated and takes into account damage produced by the laser to the missile's seeker/guidance system during its trajectory so that the missile misses its target. It should be noted that, for an air defense weapon, the laser is not effective in bad weather conditions where the relative humidity is high.

G. COMPUTER PROGRAMS FOR VULNERABILITY ASSESSMENT

The determination of an aircraft's vulnerability can be a complex and time consuming task. When done manually, many simplifications and assumptions are made, the results are subject to interpretation, and the output is usually limited in scope. Consequently, an extensive number of computer programs or models have been developed by the U.S. military and industry for assessing aircraft vulnerability. These programs can be divided into four major categories; shot-line generators, vulnerable area routines, internal burst programs, and Endgame programs. Programs in the first two categories are used for the penetrator and single fragment damage mechanisms. Those in the third category are used for internally detonating HE warheads, and those in the fourth category are for the proximity fuzed HE warhead. (The reader is cautioned that just because a computer is used,

133

the results are not to be treated as sacrosanct. The output is no more valid than the assumptions that were used to develop the model and the input data.)

Computerized techniques for vulnerability estimates for nonexplosive projectiles and single fragments are currently in wide use. A prerequisite for performing such analyses is the generation of a geometric model of the aircraft describing all of the critical components and the major structure and nonvulnerable components that provide shielding for the critical components. The computer is then programmed to project shotlines (parallel rays) through this model, from selected viewing aspects to provide a sequential listing of penetration data for input to a computerized vulnerability analysis.

1. Shotline Generators

These programs generate shotline descriptions of aircraft targets for use as input data to the codes which calculate vulnerable area. The programs usually model the aircraft external surface and the individual internal and external components either with a set of geometric shapes or with surface patches. The target geometric information required to assess the vulnerability by computer program is generated mathematically by superimposing a planar grid over the target model and by passing a large number of parallel rays through the target from the attack direction to the other side (normal to the grid) through individual grid cells, as shown in Figure 2.34. The position and number of rays is determined by means of the superimposed grid. The number of rays is controlled by selecting the size of the individual squares of the grid. One shotline is randomly located within each cell. Each ray-surface encounter is listed sequentially and identifies the ray location, surface identification number, thickness, obliquity angle, airspace

134

Figure 2.34   Example Grid for the Shotline

encountered, and distance between internal surfaces. This procedure is repeated for all shotlines originating from the selected attack directions. Also the A_p of designated components and of the overall target is output for each viewing aspect. The A_p is approximated by multiplying the number of rays intersecting the target by the area of the individual cells making up the grid plane.

Two families of shotline generator routines have been developed. They are the MAGIC, GIFT family and the SHOTGEN, FASTGEN family. The MAGIC and GIFT codes were developed at the U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD. These codes use the combinatorial geometry approach, with basic body shapes such as spheres, boxes, cylinders, ellipsoids, and cutting or bounding planes, to describe components. GIFT is an improved version of MAGIC, with simpler input requirements, more efficient computation, and computer-generated graphic displays. The second family, SHOTGEN and the more recent FASTGEN and FASTGEN II, is somewhat similar to the other family, but typically uses the flat triangular patch method to describe the component surfaces. SHOTGEN was developed by the Naval Weapons Center, and FASTGEN and FASTGEN II are improved versions of SHOTGEN sponsored by the Air Force Aeronautical Systems Division (ASD). Figure 2.35 shows the external view of a model built using the combinatorial geometry approach, and Figures 2.36 and 2.37 show the external view and some internal components of a flat triangular surface patch model, respectively.

2. Vulnerable Area Routines

These programs generate component and total aircraft vulnerable area tables for a single penetrator or fragment. The vulnerable area routines can be divided into two groups, the "detailed" or analysis routines, which use the shotline

Figure 2.35   Combinatorial Geometry Model of an Aircraft

Figure 2.36   External View of Aircraft Using
Triangular Surface Patch Method

Figure 2.37 Internal Components Modeled
Using Triangular Patch Method

139

approach to compute the vulnerable area, and the "simpli-
fied" or evaluation routines which use simplified approaches
to determine the vulnerable area. The routines in the anal-
ysis group are usually used for problems requiring in-depth
studies. However, they have the potential for use in early
design studies in which only a limited amount of technical
descriptive data is available. The evaluation routines are
more appropriate for problems in which a cursory analysis is
desired.

a. Analysis Routines

The programs VAREA, VAREA02, and COVART belong
to the detailed group. Inputs to these programs include the
shotline descriptions of the target model generated by the
shotline programs, probability of kill given a hit data for
the individual components, empirical ballistic penetration
data, and weapon characteristics data. Component and
aircraft single hit vulnerable area data are output in
tabular form.

VAREA is the oldest and least comprehensive of
the three routines in this group. It was developed in 1965
by the Naval Weapons Center to conduct vulnerability anal-
yses of systems subjected to fragmenting-type threats and
uses the THOR penetration equations to compute penetrator
mass and velocity decay due to penetration through the
components along the shotline. VAREA02, completed in 1973,
evolved from the VAREA program. Its added capabilities
include a projectile penetration mode, an air gap fire
model, a redundant components model, and an option to use
the DRI penetration equations instead of the THOR relations.

COVART (Computation of Vulnerable Area and
Repair Time) currently represents the state-of-the-art in
vulnerable area routines. It incorporates all of the
features of the VAREA02 program and the helicopter

140

vulnerable area routines from the HART program and includes
a battle damage repair time model. The procedure used by
COVART to compute single hit vulnerable areas is essentially
the same as that described in this chapter for the single
nonexplosive penetrator or fragment. The component vulner-
able area of each cell is the product of the cell presented
area and the probability of component kill for the shotline
in that cell. The vulnerable area of each component is the
sum of the component vulnerable areas computed for each grid
cell whose shotline passes through the component. The total
aircraft vulnerable area is the sum of all of the cell vuln-
erable areas, considering only the nonredundant critical
components and any redundant critical component overlap.
Both true and incremental vulnerable areas are available for
the overlapping components. Redundant critical components
that do not lie along the same shotline do not contribute to
the aircraft vulnerability.

b. Evaluation Routines

The computer program COMVAT is representative of
the routines which belong to the other group, the simplified
codes. These routines were developed to fulfill the need
for relatively quick methods for computing vulnerable area.
They are intended to be used in situations when use of the
more sophisticated routines may not be feasible or timely,
such as during early conceptual design studies. The simpli-
fied routines are not as accurate as the detailed routines,
but they should require considerably less effort and
computer run time to use.

COMVAT was developed specifically to compute the
vulnerable areas of aircraft components to projectile
threats. It is based upon the same principles as the
detailed routines, but it does not use shotline descriptions
of the aircraft; instead, it computes component vulnerable

141

areas on the basis of input data describing average shielding conditions on the components. The THOR penetration equations are used to model projectile velocity decay. Secondary effects such as spalling, projectile yawing motions, and projectile break-up are ignored.

3. Internal Burst Programs

Several programs for computing the vulnerability of aircraft to internally detonating HE warheads have been developed under the direction of the Joint Technical Coordinating Group for Munitions Effectiveness (JTCG/ME). These programs are sometimes referred to as point burst programs, and the best known program is the POINTBURST program. This program uses the second approach described in the section on vulnerability to internally detonating HE warheads which is the point burst approach.

4. Endgame Programs

The Endgame refers to the terminal events in an encounter between an aircraft and an HE warhead with a proximity fuze. Just how the warhead got to the vicinity of the aircraft is irrelevant to the Endgame analysis. The Endgame events may include target detection by the fuze, and usually do include the warhead detonation, blast propagation, and fragment flyout, impact, and penetration through the aircraft. The numerical value for the $P_{K/D}$ is then determined for the given set of encounter conditions and warhead and aircraft characteristics. This procedure is usually repeated for many different sets of encounter conditions and warhead detonation points, and $P_{K/D}$ is established as a function of the detonation distance. Four Endgame programs currently in use are SYSTEM II, SCAN, ATTACK, and REFMOD or MECA. A fifth program, SHAZAM, is nearing completion.

142

a. SESTEM II

This program was developed in 1977 by the U.S.
Air Force Aeronautical Systems Division to evaluate the
terminal effectiveness of missiles with nonnuclear blast and
fragmentation warheads against aerial targets. The P   is
computed with respect to a direct hit, fragment damage, and
blast. The program has the capability to simulate several
fuzing options and a general terminal encounter geometry.
The fragment spray angles and density, and fragment average
mass, static velocity, cross-sectional area, and coefficient
of drag are input data. The target is represented as a
collection of shapes that are either single fragment vulner-
able, masking, or fuzing components. The external shapes
(wing, fuselage, etc.) are modeled using ellipses, and
rectangular parallelpipeds are used for the internal compo-
nents, such as fuel tanks and electronics. The vulner-
ability of the components is represented by vulnerable area
tables. The program can be used to generate iso-$P_{K/D}$
contours.

b. SCAN

SCAN was developed in 1976 under the supervision
of the U.S. Navy Pacific Missile Test Center (PMTC) for the
Joint Technical Coordinating Group for Aircraft
Survivability (JTCG/AS). The objective of SCAN is to
predict the probability that an aircraft will survive an
attack by a missile armed with a warhead. Aircraft kills
due to direct hit, fragment damage, and blast are evaluated.
A few fuzing options are considered, as well as a general
terminal encounter geometry. The warhead is divided into
polar and radial zones and different fragment sizes, shapes,
and materials can be specified within each zone. The target
is modeled using the combinatorial geometry approach, and
component vulnerability to single fragments is expressed by:

143

$$P_{k/h} = C_1 + [C_2 \text{ x Mass}] + [C_3 \text{ x Velocity}] \qquad (2.73)$$

where mass and velocity refer to the fragment mass and
velocity. The energy density and area removal kill criteria
are also options for use with components such as major
structures. Each component is given a material and thick-
ness and is linked to a subsystem, system, or aircraft kill
by a logical kill expression, thus allowing the considera-
tion of redundancy. SCAN also has graphics capabilities for
evaluation of the input geometric model and output fragment
impact data.

c. ATTACK

ATTACK is a Naval Weapons Center revision of an
Endgame methodology developed at the Naval Missile Center,
Point Mugu. The object of ATTACK is to predict the ability
of a missile to detect and destroy an airborne target.
Direct hit, blast, and single fragment (component), and
multiple fragment (structural) kills are considered, and a
general terminal encounter geometry is provided. The
warhead in ATTACK uses the concept of polar and radial frag-
ment spray zones and fragment weight classes. A large
number of fuze options are available. The program requires
four target models, one for each type of damage, and one
fuze model for each encounter. The components in the single
fragment model are physically represented by spheres at
specified locations, and the vulnerability of each component
is contained in vulnerable area tables that depend upon
aspect angle, fragment mass, and fragment impact velocity.
The multiple fragment model uses a segmented cylindrical
target representation, and the vulnerability of each segment
is specified by a critical level of fragment energy density.

d. REFMOD (MECA)

The REFMOD program, developed in 1981, was intended to be a reference model to be used for computing the effectiveness of externally detonating weapons against moving targets. (It was later renamed Modular Endgame Computer Analysis or MECA). The model was developed under the auspices of the JTCG/ME Anti-Air Missile Evaluation Group. REFMOD has been assembled by incorporating methodologies from many other existing Endgame programs, including some significant additional features that enable it to work with a wide variety of vulnerability models and to evaluate warhead-target combinations that were previously too cumbersome to assess. The warhead types considered include the continuous rod, divergent fragment spray, convergent fragment spray, focused fragment controlled motion, and an aimable warhead in which the fragment spray density is non-uniform about the missile axis. Several fuze routines are available, and the option exists for the specification of fuzing data from flight tests. The target model and vulnerability employed depend upon the damage mechanism selected. These include direct hit, blast, fragment, and continuous rod. Component vulnerability types for fragments include both vulnerable area and a $P_{k/h}$ kill criterion that is a function of mass, velocity, and density. For the vulnerable area model, components can be described as spherical, linear, cylindrical, or planar in shape, and the component vulnerable area tables generated by COVART can be used. The $P_{k/h}$ vulnerability model employs cylindrical components, and the component kill criterion is given by:

$$P_{k/h} = C_1 \times (\text{Mass})^{C_2} \times (\text{Velocity})^{C_3} \qquad (2.74)$$

145

with lower and upper threshold values. By inputting different values for C_1, C_2, and C_3, a variety of kill criteria can be employed. For example, when $C_1 = 0.5$, $C_2 = 1$, and $C_3 = 2$, the energy density criterion is specified.

e. SHAZAM

This code was developed at the Air Force Armament Laboratory (AFATL/DLY) for the evaluation of air-to-air missile effectiveness. The program sequentially assesses the possibility the target aircraft is directly impacted by the missile, the effect of blast overpressures upon the target structures, and the cumulative effect of warhead fragment impacts on the target structure and critical components. The size, shape, and position of the target body and internal components are described by discrete surfaces, and each surface can be vulnerable to a direct hit, to blast, or to fragments. The criteria used to define the kill of each component/surface are supplied by the user. The program utilizes as much of the aircraft descriptions that are prepared for the SHOTGEN and VAREA programs as is economically feasible. A sufficiently large number of encounter conditions are assessed to generate a single shot probability of kill that has converged to a user specified confidence level.

BIBLIOGRAPHY

Ball, R. E., Fundamentals of Aircraft Combat Survivability Analysis and Design, Naval Postgraduate School, June 1984, (Unpublished).

Ballistic Research Laboratory, BRL Report No. 1796, Aircraft Vulnerability Assessment Methodology, Volume I-General, by D. Mowrer, et. al., July 1975.

Department of Defense, JTCG/AS, JTCG/AS-75-V-008, Required Minimum Elements of a JTCG/AS Vulnerability Assessment, by G. B. Bennett, December 1976.

Department of Defense, JTCG/AS, JTCG/AS-77-V-002, Vulnerability Test Guidelines and Requirements, by E. W. Stull, June 1980.

Department of Defense, JTCG/ME, JTCG/ME-73-3, Internal Blast Damage Mechanisms Computer Program, by J. F. Proctor, April 1973.

Department of Defense, JTCG/ME, JTCG/ME-75-5, Dynamic Air-to-Air Model Computer Program Volume I-Users Manual, by Joint Technical Coordinating Group for Munitions Effectiveness, March 1975.

Department of Defense, JTCG/ME, JTCG/ME-75-14-2, Complex Targets Computer Program Volume II-Analyst Manual, by Joint Technical Coordinating Group for Munitions Effectiveness, June 1979.

Naval Weapons Center, TN 4565-12-73, Derivation of Structural Damage Prediction Formulae for Multiple Fragment Damage Mechanisms, by M. D. Alexander, March 1974.

INITIAL DISTRIBUTION LIST

		No. Copies
1.	Library, Code 0142 Naval Postgraduate School Monterey, California 93943	2
2.	Department Chairman Code 67P1 Department of Aeronautics Naval Postgraduate School Monterey, California 93943	1
3.	Professor Robert E. Ball Code 67BP Department of Aeronautics Naval Postgraduate School Monterey, California 93943	2
4.	Distinguished Professor Allen E. Fuhs Code 67FU Department of Aeronautics Naval Postgraduate School Monterey, California 93943	1
5.	Defense Technical Information Center Cameron Station Alexandria, Virginia 22314	2
6.	LTJG Sukij Sarararung, RTN Naval Ordnance Department Royal Thai Navy Bangna, Bangkok #10260 Thailand	1

END

DATE
FILMED

7-85

DTIC